



Frameless Glass Display

Sleek square canopy design with 8mm tempered glass for full visibility and modern presentation.



Ample Rear Storage

Rear refrigerated section allows for efficient stock handling and quick product replenishment.



Easy Access Front Glass

Hinged front glass opens up to 32° for fast and convenient cleaning or loading.



Advanced Cooling System

Fan-forced cooling and EBM fans maintain consistent, even temperature across the entire cabinet.

DETAILS

The STK/ST-LK Range is a compact yet high-performance deli display range, ideal for smaller retail or foodservice operations. With a modern frameless glass canopy, intuitive front access, and generous rear storage, these units are designed for function and form. Fan-forced airflow and precise

temperature control ensure optimal product preservation, while thoughtful features like LED lighting and bumper protection enhance both presentation and durability. Perfect for chilled meats, cheeses, and fresh prepared goods.







FEATURES

INTERNAL LED LIGHTING FOR PREMIUM PRODUCT DISPLAY

Bright, energy-efficient lighting enhances visibility and draws attention to your products

STYLISH INTERNAL GLASS SHELF FOR AMBIENT DISPLAY

Adds a second tier for nonrefrigerated product presentation within the case

SELF-EVAPORATIVE DRAINAGE FOR LOW-MAINTENANCE OPERATION

Reduces manual water removal, ensuring easy, hassle-free maintenance

PROTECTIVE BUMPER BAR FOR EXTRA DURABILITY

Shields the cabinet from accidental knocks in busy service environments

THICK TEMPERED SAFETY GLASS

8mm glass provides durability, safety, and a clear view of displayed items

DIXELL CONTROLLER FOR PRECISE TEMPERATURE CONTROL

Allows accurate and reliable adjustment of storage temperatures



Frameless glass canopy for maximum visibility

Stylish glass shelf for ambient display

Front glass opens to 32° for quick service

Easy to maintain with a slide-out condensing

Rear Refrigerated Storage

Product Code	Dimensions (WxDxH mm)	Temp Range (°C)	Ambient temp/RH%	Voltage (V)	Power (W/A)	Display Area (m²)
Full Models						
STK1312	1330x1164x1235	-2 to +2°C	25°C60%	415	550/10	0.88
STK2012	1955x1164x1235	-2 to +2°C	25°C60%	415	980/10	1.16
STK2612	2580x1164x1235	-2 to +2°C	25°C60%	415	1060/10	1.45
Compact models						
ST15LK	1580x940x1200	0 to +5°C	25°C60%	415	430/10	0.73
ST20LK	1955x940x1200	0 to +5°C	25°C60%	415	440/10	0.95
ST25LK	2580x940x1200	0 to +5°C	25°C60%	415	540/10	1.26





