



## FED-X S/S Single Full Door Upright Fridge - XURC600SFV

### Quick Overview

- Gross Volume: 618L
- Net Volume: 396L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -2 to +8°C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H

Â

### Description

FED-X S/S Single Full Door Upright Fridge - XURC600SFV

### Key Features

- Gross Volume: 618L
- Net Volume: 396L

- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -2 to +8 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs-free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H
- Certified 4M1 food-safe with a 3 Star GEMS rating

**2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice**

Your Shipping Specifications

|                          |                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------|
| Product Condition        | New                                                                                             |
| Doors                    | 1                                                                                               |
| Door Type                | Hinged Doors                                                                                    |
| Body                     | Stainless Steel                                                                                 |
| Gross Volume             | 618L                                                                                            |
| Net Volume               | 396L                                                                                            |
| Max Ambient Temperature  | 43°C, 60%RH                                                                                     |
| Temperature Range        | -2 to +8 ° C                                                                                    |
| Total Energy Consumption | 2.22 kWh/24h                                                                                    |
| Net Weight (Kg)          | 115                                                                                             |
| Width (mm)               | 680                                                                                             |
| Depth (mm)               | 810+30                                                                                          |
| Height (mm)              | 2000                                                                                            |
| Packing Width (mm)       | 765                                                                                             |
| Packing Depth (mm)       | 855                                                                                             |
| Packing Height (mm)      | 2070                                                                                            |
| Power                    | 240V, 195W/10A                                                                                  |
| Warranty                 | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |