



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Thermaster TL1200TN Stainless Steel Double Door Workbench Fridge – 250L

Model / SKU: TL1200TN

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/4546/store/7/



Thermaster Stainless Steel Double Door Workbench Fridge - TL1200TN

Quick Overview

- 700 Series
- Gross Volume: 250L
- Net Volume: 202L
- Max Ambient Temperature: 32°C
- Temperature Range: -2 to +8 ° C
- Solid Door fridge Ambient 43°C
- Fan-forced evaporator cooling
- Auto defrost
- Self-evaporating drainage
- Insulation is CFC & HCFC-free
- Internal corners are constructed for easy cleaning
- 100mm wall clearance is required for ventilation
- Castors
- Dimension: 1200mmW x 700D x 810H;
- Power: 240V; 219W; 10A outlet required

Â

Description

Thermaster Stainless Steel Double Door Workbench Fridge - TL1200TN

Features

- 700 Series
- Gross Volume: 250L
- Net Volume: 202L
- Max Ambient Temperature: 32
- Temperature Range: -2 to +8 ° C
- Solid Door fridge Ambient 43°C
- Fan-forced evaporator cooling
- Auto defrost
- Self-evaporating drainage
- Insulation is CFC & HCFC-free
- Internal corners are constructed for easy cleaning

- 100mm wall clearance is required for ventilation
- Castors
- Dimension: 1200mmW × 700D × 810H;
- Power: 240V; 219W; 10A outlet required

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	250L
Net Volume	202L
Max Ambient Temperature	32
Temperature Range	-2 to +8 ° C
Total Energy Consumption	2.69 kWh/24h
Net Weight (Kg)	90
Width (mm)	1200
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	730
Packing Depth (mm)	1240
Packing Height (mm)	900
Power	240V; 250W; 10A Outlet Required
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice