



Fagor Electric conveyor dishwasher - CCO-120DCW

Quick Overview

- All AISI-304 Stainless steel
- Upwards-opening double panel door
- Easy access for cleaning
- Safety filter for pump suction
- Rinsing boiler with heat insulation
- Easy access for installation
- Electrical panel designed for easy connection of dosers for liquid and solid detergents, rinse aid, limit switches,
- Washing arms easily removable as a set, for cleaning
- Rinse jets easily dismountable and removable.
- Wash (50 - 65 ° C)
- Rinse (70 - 85 ° C)
- Emergency stop button incorporated.
- Open door blocking system
- IPX4 protection system
- System for detection of blockage of conveyor carriage and automatic reverse function.
- High-power washing system with 4 upper and 4 lower washing branches
- 3 washing programs: deep, medium and high capacity
- Double effect rinse.
- Energy-saving systems
- Included: 2 base baskets; 2 baskets for plates; 1 basket for glasses; 1 basket for cutlery
- Watermark approved

Description

Fagor Electric conveyor dishwasher - CCO-120DCW

Key Features

COMPACT RACK CONVEYOR DISHWASHER

- All AISI-304 Stainless steel
- Upwards-opening double panel door
- Easy access for cleaning
- Safety filter for pump suction
- Rinsing boiler with heat insulation
- Easy access for installation
- Electrical panel designed for easy connection of dosers for liquid and solid detergents, rinse aid, limit switches,
- Washing arms easily removable as a set, for cleaning
- Rinse jets easily dismountable and removable.
- Wash (50 - 65 ° C)
- Rinse (70 - 85 ° C)
- Emergency stop button incorporated.
- Open door blocking system
- IPX4 protection system
- System for detection of blockage of conveyor carriage and automatic reverse function.
- High-power washing system with 4 upper and 4 lower washing branches
- 3 washing programs: deep, medium and high capacity
- Double effect rinse.
- Energy-saving systems
- Included: 2 base baskets; 2 baskets for plates; 1 basket for glasses; 1 basket for cutlery
- Watermark approved
- Dimensions (WxDxH mm): 1180x790x1550

2 Years Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	211
Width (mm)	1180
Depth (mm)	790
Height (mm)	1550
Packing Width (mm)	960
Packing Depth (mm)	1530
Packing Height (mm)	1900
Power	415/50 V/Hz;28.45/3-N kW/A
Warranty	2 Years Parts and Labour