



FED-X S/S Two Full Glass Door Upright Freezer - XURF1410G2V

Quick Overview

- Gross Volume: 1410L
- Net Volume: 945L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature Range: -15 to -18 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- User-friendly Digital controls and internal lighting
- Heated door frame for freezer unit
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H

Description

FED-X S/S Two Full Glass Door Upright Freezer - XURF1410G2V

Key Features

- Gross Volume: 1410L
- Net Volume: 945L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature Range: -15 to -18 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- User-friendly Digital controls and internal lighting

- Heated door frame for freezer unit
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	1410L
Net Volume	945L
Max Ambient Temperature	38°C, 60%RH
Temperature Range	-15 to -18 ° C
Total Energy Consumption	10.33 kWh/24h
Lids	2
Form Factor	Upright
Lid Material	Glass
Net Weight (Kg)	232
Width (mm)	1480
Depth (mm)	860
Height (mm)	2000
Packing Width (mm)	1505
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 865W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice