

UPRIGHT GLASS DOOR COOLER

CIRCUIT DIAGRAM

Legend:

- BN: Bottom Neutral
- BU: Bottom Unearthed
- YE/GN: Yellow/Green ground

MODEL	LG-730P
CLIMATIC CATEGORY	T
PROTECTIVE CLASSIFICATION OF ELECTRIC SHOCK RESISTANCE	II
INSULATION BLOWING GAS	Cyclopentane
TOTAL CAPACITY	730L
RATED VOLTAGE	240V
RATED FREQUENCY	50Hz
RATED CURRENT	3.4A
RATED POWER INPUT	450W
DEFROST POWER INPUT	-
LIGHT POWER	26W
REFRIGERANT	R290(105g)
ENERGY CONSUMPTION	4.5kWh/24h
NET WEIGHT	113kg

CB CE GEMS

MODEL	LG-730P
CLIMATIC CATEGORY	7
PROTECTIVE CLASSIFICATION OF ELECTRIC SHOCK RESISTANCE	I
INSULATION BLOWING GAS	Cyclopentane
TOTAL CAPACITY	730L
RATED VOLTAGE	240V
RATED FREQUENCY	50Hz
RATED CURRENT	3.4A
RATED POWER INPUT	450W
DEFROST POWER INPUT	/
LIGHT POWER	26W
REFRIGERANT	R290(105g)
ENERGY CONSUMPTION	4.5kWh/24h
NET WEIGHT	113kg