



FED-X S/S Four Door Bench Fridge - XUB7C22S4V

Quick Overview

- Gross Volume: 553L
- Net Volume: 415L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -2 to 8 ° C
- Cooling System: Fan-forced cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditioner-friendly Digital controls
- Rapid recovery rate
- Optional 2 a3-drawer units were available in lieu of doors
- EBM-PAPST evaporator and condenser Heavy-duty castors with front-wheel brake unit that can be placed against the wall
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1669mm W x 580mm D x 564mm H

Description

FED-X Stainless Steel Four Door Bench Fridge - XUB7C22S4V

Key Features

- Gross Volume: 553L
- Net Volume: 415L

- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -2 to 8 °C
- Cooling System: Fan-forced cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditioner-friendly Digital controls
- Rapid recovery rate
- Optional 2 a3-drawer units were available in lieu of doors
- EBM-PAPST evaporator and condenser Heavy-duty castors with front-wheel brake unit that can be placed against the wall
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1669mm W x 580mm D x 564mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	4
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	553L
Net Volume	415L
Max Ambient Temperature	43 °C, 60%RH
Temperature Range	-2 to 8 °C
Total Energy Consumption	5.176 kWh/24h
Net Weight (Kg)	340
Width (mm)	2230
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	2260
Packing Depth (mm)	730
Packing Height (mm)	910
Power	240V; 345W/2.0A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice