



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

ElectMax EIC9-1200P 900 Series 6-Burner Induction Cooker – 1200mm, 30kW

Model / SKU: EIC9-1200P

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://www.foodequipment.com.au/amfile/file/download/file/4540/product/7671/>

ELECT MAX

700/900 Range Induction Cooking/Griddle/Fryer

IC9-4B

EIC7-400P EIC7-800P EIC7-1200P

EIC9-400P EIC9-800P EIC9-1200P

EGP7-800 EGP9-800

IFS7-30L IFS10-30L



Scalable Strength for Serious Kitchens.

ELECT MAX delivers powerful induction heating for fast, energy-efficient cooking. Features intuitive touch controls with timers and safety protection. Built with durable stainless steel for easy cleaning and long-lasting use. Available in flexible sizes to suit any commercial kitchen.

User-Friendly Controls



Touchscreen or touch and knob interfaces with timers and safety features.

Durable Stainless Steel Construction



Commercial-grade 304 stainless steel ensures longevity and easy cleaning.

High-Powered Induction Heating



Delivers rapid, energy-efficient heating with precise temperature control.

Versatile and Scalable Design



Multiple sizes and configurations to suit various professional kitchen needs.

FEDERAL
HOSPITALITY EQUIPMENT



AUS Phone: 1300 659 409
Email: sales@foodequipment.com.au
www.foodequipment.com.au



NZ Phone: 09 415 6470
Email: sales@fedproducts.co.nz
www.fedproducts.co.nz

700/900 Range Induction Cooking



EIC7-400P/EIC9-400P



EIC7-800P/EIC9-800P



EIC7-1200P/EIC9-1200P

Code	Dimensions (WxDxH mm)	Weight (kg)	Temperature (°C)	Voltage (V)	Power (kW/A)
EIC7-400P	400x700x1003	36	+60 to +240	415	10/3~N
EIC7-800P	800x700x1003	60	+60 to +240	415	20/3~N
EIC7-1200P	1200x700x1003	84	+60 to +240	415	30/3~N
EIC9-400P	400x900x1003	50	+60 to +240	415	10/3~N
EIC9-800P	800x900x1003	75	+60 to +240	415	20/3~N
EIC9-1200P	1200x900x1003	100	+60 to +240	415	30/3~N

Induction 4 Burner Cooker with Convection Oven



IC9-4B

700/900 Range Induction Griddle



EGP7-800/EGP9-800

700/900 Range Induction Fryer



IFS7-30L/IFS9-30L

Code	Dimensions (WxDxH mm)	Oven Dimensions (WxDxH mm)	Weight (kg)	Oven Temp Range (°C)	Voltage (V)	Oven Power (kW)	Power (kW/A)
IC9-4B	800x900x891	570x700x300	132	50 to 300	415	4.5	10/3~N

Code	Dimensions (WxDxH mm)	Weight (kg)	Temperature (°C)	Voltage (V)	Power (kW/A)
EGP7-800	800x700x1003	103	+80 to +300	415	10/3~N
EGP9-800	800x900x1003	118	+80 to +300	415	10/3~N
IFS7-30L	400x700x1003	55	-	415	10/3~N
IFS9-30L	400x900x1003	57	-	415	10/3~N