



FED-X S/S Full Glass Door Upright Fridge - XURC600G1V

Quick Overview

- Gross Volume: 618L
- Net Volume: 388L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature range: +2 to +8 ° C
- Cooling System Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulations-friendly Digital controls and internal lightish shelf elf and shelf support are designed to accommodate the 2 x 1/1 GN Heavy-duty evaporator and condenser fanHeavy-duty castors with front-wheel brakes.
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H

Description

FED-X S/S Full Glass Door Upright Fridge - XURC600G1V

Key Features

- Gross Volume: 618L
- Net Volume: 388L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature Range: +2 to +8 ° C
- Cooling System Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- Internal LED lighting
- HFCs and CFCs free foam body insulations-friendly Digital controls and internal lightish shelf elf and shelf support are designed to accommodate the 2 x 1/1 GN Heavy-duty evaporator and condenser fanHeavy-duty castors with front-wheel brakes.

- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	1
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	618L
Net Volume	388L
Max Ambient Temperature	38°C, 60%RH
Temperature Range	+2 to +8 ° C
Total Energy Consumption	3.208 kWh/24h
Net Weight (Kg)	132
Width (mm)	680
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 195W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice