



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Fagor FMD-2301A Meat Aging Cabinet – UV Sterilised, Humidity-Controlled

Model / SKU: FMD-2301A

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://www.foodequipment.com.au/amfile/file/download/file/868/product/6418/>



Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
FMD-2301-W-L-W-BLA TR 230V 1N 50/60Hz

19092414

05/04/2022

DENOMINATION:

Dry-aging meat cabinet Meat Ager Advance FMD-2301-W-L-W-BLA TR 2300 mm height 1 door wall configuration door opening to the left white led lighting black color finishing 230V 1N 50/60 Hz climate class V cold group included refrigerant gas R455a

DESCRIPTION :


- Dry aging cabinet specially designed to age, display and distribute meat.
- Fully manufactured in stainless steel for intensive professional use.
- Side and central walls with double-layered glass and air chamber between them.
- Swing doors that optimize space usage and make work easier.
- One (1) digital thermostat for temperature and humidity control.
- Refrigeration system adjustable between 0 and +20°C with increments of 0.1°C.
- Ventilated refrigeration system to obtain a homogeneous temperature inside the cellar.
- Ultraviolet light for air sterilization.
- Tray to collect defrost water and automatic evaporation. No drain required.
- Thermostat to adjust humidity between 60 and 90%.
- LED lighting in all perimeters, adjustable by remote control.
- For easy delivery, dry-aging cabinets are shipped in two sections: body and removable top section containing complete refrigeration unit.
- Decorative plinth included as a standard element. Shelves and hooks should be requested separately and are supplied disassembled.
- Glasses and door frames heated to avoid condensations.

POSSIBLE ACCESSORIES :

- ACCESSORIES
- PERFORATED MEAT SHELF
- BAR
- HOOK
- PINK SALT

DIMENSIONS

X Width	862 mm	X Gross width	1005 mm
Y Depth	632 mm	Y Gross depth	800 mm
Z Height	2300 mm	Z Gross height	2685 mm
Net Weight	272,0 kg	Gross Weight	284,0 kg
Net volume	1,253 m3	Gross volume	2,159 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	1,740 kW
Amperage (A)	7,7A
Voltage	230V - 1N
Electric frequency	50/60Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R455A
----------	-------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,950 kW
Gross internal volume	605 L
Climate class	4
Cooling gas load	320,000 g

CONNECTIONS TECHNICAL SPECIFICATIONS

Drain 1 diameter	1/2"
------------------	------

OTHERS

Colour	Black
Number of doors	1
Type	Wall type
N° temperatures	1
Door opening	Left
LED colour	Warm white 2700°K



www.fagorprofessional.com



Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
FMD-2301-W-L-W-BLA TR 230V 1N 50/60Hz

19092414

05/04/2022

