



FED-X S/S Split Two-Door Upright Fridge - XURC650S1V

Quick Overview

- Gross Volume: 650L
- Net Volume: 465L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -2 to +8°C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running costs by up to 30%

Description

FED-X S/S Split Two-Door Upright Fridge - XURC650S1V

Key Features

- Gross Volume: 650L

- Net Volume: 465L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -2 to +8 °C
- Cooling System: Fan-Forced cooling
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm-compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs-free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pans
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running costs by up to 30%
- Certified 4M1 food-safe with a 3 Star GEMS rating

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	650L
Net Volume	465L
Max Ambient Temperature	43 , 60%RH
Temperature Range	-2 to +8 ° C
Total Energy Consumption	2.69 kWh/24h
Net Weight (Kg)	121
Width (mm)	740
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 310W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice