



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

F.H.E Tecnodom TDE-3BG 3-Tray Convection Oven with Grill

Model / SKU: TDE-3BG

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/8248/store/7/



Tecnodom Nerone EKO 600x400 Tray Convection Oven with Grill - TDE-3BG

Quick Overview

- 1 Tray Convection Oven 600x400mm Tray
- Stainless steel cooking chamber with rounded corners
- Tempered low-e glass
- Overture Folding Door offers an innovative, high-performance door solution for large opening applications
- Interlocking gasket fixing system
- According to the IPX3 standard norms
- High resistance hinge
- Temperature range of +50 to +280°C
- 60-minute timer or infinite
- 105mm distance between trays
- Machine Dimension 775x720x560 mm
- Net weight: 40kg
- Internal Dimension: 650x459x350 mm
- Power: 3,15 kW / 1,7 kW Grill, 15A
- Voltage: 240V
- Grill and Grill + Convection Function
- Includes: 1 solid tray and 2 wire racks

Description

Tecnodom Nerone EKO 600x400 Tray Convection Oven with Grill - TDE-3BG

Products studied to achieve optimal operations and performance for modern catering.

Tecnodom introduces the NERONE range of ovens, dedicated to excellence in cooking systems. The technological, planning, and design skills used by Tecnodom are synthesized in the NERONE range of ovens. The company, therefore, offers products that align with market needs and combine essentiality and simplicity in cleaning and maintenance.

Key Features

- 1 Tray Convection Oven 600x400mm Tray
- Stainless steel cooking chamber with rounded corners
- Tempered low-e glass
- Overture Folding Door offers an innovative, high-performance door solution for large opening applications
- Interlocking gasket fixing system
- According to the IPX3 standard norms
- High resistance hinge
- Temperature range of +50 to +280 ° C
- 60-minute timer or infinite
- 105mm distance between trays
- Machine Dimension 775x720x560 mm
- Net weight: 40kg
- Internal Dimension: 650x459x350 mm
- Power: 3,15 kW / 1,7 kW Grill, 15A
- Voltage: 240V
- Grill and Grill + Convection Function
- Includes: 1 solid tray and 2 wire racks

1 Year Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Knobs	3 knobs
Net Weight (Kg)	40
Width (mm)	775
Depth (mm)	720
Height (mm)	560
Packing Width (mm)	750
Packing Depth (mm)	800
Packing Height (mm)	730
Power	240V, 3,15kW / 1,7kW Grill, 15A
Warranty	1 Year Parts and Labour Warranty