



FED-X S/S Single Door Upright Fridge - XURC650SFV

Quick Overview

- Gross Volume: 650L
- Net Volume: 465L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -1 to +5°C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H

Description

FED-X S/S Single Door Upright Fridge - XURC650SFV

Key Features

- Gross Volume: 650L
- Net Volume: 465L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -1 to +5

- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	1
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	650L
Net Volume	465L
Max Ambient Temperature	43 , 60%RH
Temperature Range	-1 to +5
Total Energy Consumption	2.69 kWh/24h
Net Weight (Kg)	134
Width (mm)	740
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V, 215W/1.4A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice