



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Fagor CP-E7226 Electric Pasta Cooker – 4 Baskets, 18kW

Model / SKU: CP-E7226

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/8188/store/7/



Fagor Kore 700 Series Electric Pasta Cooker with 4 Baskets CP-E7226

Quick Overview

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing
- Hidden screws
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top
- Wells that suit different arrangements and measures of baskets
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow
- Automatic safety system to stop the current if the water runs out
- Controls with a protective support base and system to prevent water infiltration
- Access to components from the front
- Stainless steel feet with adjustable height
- Machines with IPX5 grade water protection
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level)
- Burner ignition through electronic spark igniter. With an access tube for manual ignition
- Heating controlled through safety valve

Description

Fagor Kore 700 Series Electric Pasta Cooker with 4 Baskets CP-E7226

Key Features

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing
- Hidden screws
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top
- Wells that suit different arrangements and measures of baskets
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow
- Automatic safety system to stop the current if the water runs out
- Controls with a protective support base and system to prevent water infiltration
- Access to components from the front
- Stainless steel feet with adjustable height
- Machines with IPX5 grade water protection
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level)
- Burner ignition through electronic spark igniter. With an access tube for manual ignition
- Heating controlled through safety valve

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Knobs	4 knobs
Net Weight (Kg)	85
Width (mm)	800
Depth (mm)	730
Height (mm)	850
Packing Width (mm)	822
Packing Depth (mm)	840
Packing Height (mm)	1255
Power	415V, 18kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice