



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

FED-X XUB6F13S2V Stainless Two Door Bench Freezer – 228L, R290, Digital

Model / SKU: XUB6F13S2V

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/5237/store/7/



FED-X S/S Two Door Bench Freezer - XUB6F13S2V

Quick Overview

- Gross Volume: 228L
- Net Volume: 170L
- Max Ambient Temperature: 38°C; 60%RH
- Temperature Range: -18 to -22 ° C
- Cooling System: Fan-forced cooling
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- The unit can be placed against a wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 799mm W x 480mm D x 564mm H

Â

Description

FED-X Stainless Steel Two Door Bench Freezer - XUB6F13S2V

Key Features

- Gross Volume: 228L
- Net Volume: 170L
- Max Ambient Temperature: 38°C, 60%RH
- Temperature Range: -18 to -22 ° C
- Cooling System: Fan-forced cooling
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- The unit can be placed against a wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 799mm W x 480mm D x 564mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	228L
Net Volume	170L
Max Ambient Temperature	38°C, 60%RH
Temperature Range	-18 to -22 ° C
Total Energy Consumption	7.566 kWh/24h
Lids	2
Form Factor	Workbench
Lid Material	Solid
Net Weight (Kg)	107
Width (mm)	1360
Depth (mm)	600
Height (mm)	850
Packing Width (mm)	1390
Packing Depth (mm)	630
Packing Height (mm)	910
Power	240V; 50V; 10A; 520W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice