



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Tecnodom Nerone EKO Digital 4-Tray Oven – TDE-4CD/15

Model / SKU: TDE-4CD/15

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/8323/store/7/



Tecnodom Nerone EKO Digital 435x350 Tray Convection Oven - TDE-4CD/15

Quick Overview

- Stainless steel cooking chamber with rounded corners
- Tempered low-e glass
- Fan/s stops when the door is open
- Internal lighting with a halogen lamp
- Interlocking gasket fixing system
- According to the IPX3 standard norms
- High resistance hinge
- Temperature range of +50 to +280°C
- 60-minute timer or infinite
- Double Fan
- Reliable and well-protected digital control panel, easy to use
- Memory for recipes
- Double display
- 84mm distance between trays, 105mm for TDE-3BD
- Non-slip feet
- Memory for 9 recipes
- Includes: 1 solid tray and 3 wire racks

Â

Description

Tecnodom Nerone EKO Digital 435x350 Tray Convection Oven - TDE-4CD/15

Products studied to achieve optimal operations and performance for modern catering.

Tecnodom introduces the NERONE range of ovens, dedicated to excellence in cooking systems. The technological, planning, and design skills used by Tecnodom are synthesized in the NERONE range of ovens. The company, therefore, offers products that align

with market needs and combine essentiality and simplicity in cleaning and maintenance.

Key Features

- Stainless steel cooking chamber with rounded corners
- Tempered low-e glass
- Fan/s stops when the door is open
- Internal lighting with a halogen lamp
- Interlocking gasket fixing system
- According to the IPX3 standard norms
- High resistance hinge
- Temperature range of +50 to +280 ° C
- 60-minute timer or infinite
- Double Fan
- Reliable and well-protected digital control panel, easy to use
- Memory for recipes
- Double display
- 84mm distance between trays, 105mm for TDE-3BD
- Non-slip feet
- Memory for 9 recipes
- Includes: 1 solid tray and 3 wire racks

Additional Information

- External Dimensions (WxDxmm): 589x680x580
- Internal Dimensions (WxDxmm): 464x420x370

1 Year Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	33
Width (mm)	589
Depth (mm)	680
Height (mm)	580
Packing Width (mm)	720
Packing Depth (mm)	625
Packing Height (mm)	750
Power	240V, 2.35kW/15A
Warranty	1 Year Parts and Labour Warranty