



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Woodson Mobile Ventilation Station W.MVS850 - Portable Ductless Exhaust Hood

Model / SKU: W.MVS850


KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: /home/sarah/kw_system/07_Content_Library/product_db/supplier raw data/stoddart_extracted/16_Woodson/Data Sheets/

Product Information

- Improves cooking environments where ducted local exhaust systems are not required by the National Construction Code (NCC)
- Reduces greasy deposits forming on benches, floors, walls and ceilings from cooking activities
- Improves the air quality for kitchen staff by capturing the cooking emissions and filtering the air for recirculation within the workspace
- Air is drawn down the rear of the unit through multistage filters and then returned to the kitchen through the base of the unit
- Storage area below cooking zone
- Lockable swivel castors to front and fixed castors on rear of unit for extra mobility
- 12-month onsite warranty

Application

- Woodson Mobile Filtration Systems are to be used with electric cooking appliances only.
- Use this unit with countertop electrical cooking appliances that do not exceed limits defined in the NCC* (NCC -2022 Part F6D12):
A commercial kitchen must be provided with a kitchen exhaust hood complying with AS 1668.1 and AS 1668.2 where: any cooking apparatus has a total maximum electrical power input exceeding 8 kW; or the total maximum power input to more than one apparatus exceeds 0.5 kW electrical power per m² of floor area of the room or enclosure
- Check with local authorities for any regulations that they may have in addition to the ventilation requirements of the NCC*





Important

- The unit cannot be used for gas equipment
- The unit does not remove heat or humidity from the room
- The unit must be installed as per instructions
- The Cooking equipment must be positioned correctly under the hood
- The filters will not remove very fine particulates such as smoke
- The filters must be inspected and changed or maintained regularly in order to ensure the hood continues to perform as designed

Specifications

Model	W.MVS	W.MVS850
W x D x H (mm)	700 x 775 x 1200	850 x 800 x 1200
Total Connected Load	0.48kW	0.48kW
Electrical Connection	240VAC / 50Hz (10A plug & lead)	240VAC / 50Hz (10A plug & lead)

*The NCC requires the room to be adequately ventilated, either naturally or mechanically to maintain the indoor air quality within defined limits. The room may be naturally ventilated if it has sufficient open window space. When the room has mechanical ventilation, the ventilation designer will need to provide performance evidence that an adequate supply of outdoor air into the enclosure is available to maintain the indoor air quality.



www.stoddart.com.au
www.stoddart.co.nz

Revision: B - 19/09/2025 - 08

Due to continuous product research and development, the information contained herein is subject to change without notice.

