



Ex-Showroom: FED-X S/S Four Door Upright Fridge - XURC1410S2V

Quick Overview

Lot Number: NSW1282

Class: 1

Conditions: Unit inspected new but no box

Warranty: 1 Year

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation

Description

Lot Number: NSW1282

Class: 1

Conditions: Unit inspected new but no box

Warranty: 1 Year

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation

FED-X Stainless Steel Four Door Upright Fridge - XURC1410S2V

- Net Capacity: 1410L
- Cooling System: Fan forced cooling
- Temperature range: -2 ° ~+8 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

Your Shipping Specifications

Product Condition	2ND
Net Weight (Kg)	188
Width (mm)	1480
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	1505
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 500W