



## 2NDs: FED-X S/S Two Door Upright Freezer XURF650S1V-NSW1734

### Quick Overview

Lot Number: NSW1734

Class: 2

Conditions: Unused unit. The top of the unit has been crushed on the rear. This damage causes light condensation around the damage—internal scratching on the unit's base. The hinges are bent slightly, but this doesn't affect the doors. The unit has been tested and is functioning correctly.

Warranty: 6 months

### Description

2NDs: FED-X S/S Two Door Upright Freezer XURF650S1V-NSW1734

Lot Number: NSW1734

Class: 2

Conditions: Unused unit. The top of the unit has been crushed on the rear. This damage causes light condensation around the damage—internal scratching on the unit's base. The hinges are bent slightly, but this doesn't affect the doors. The unit has been tested and is functioning correctly.

Warranty: 6 Months

### Key Features:

- Net Capacity: 465L
- Cooling System: Fan-forced cooling
- Temperature range: -18 to 22 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2a x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes

- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 624mm W x 702mm D x 1401mm H
- 1/A 2 split door system can lower yearly running cocostsy up to 30%

Your Shipping Specifications

|                     |                      |
|---------------------|----------------------|
| Product Condition   | 2ND                  |
| Capacity (L)        | 465L                 |
| Net Weight (Kg)     | 126                  |
| Width (mm)          | 740                  |
| Depth (mm)          | 830                  |
| Height (mm)         | 2000                 |
| Packing Width (mm)  | 765                  |
| Packing Depth (mm)  | 855                  |
| Packing Height (mm) | 2070                 |
| Power               | 240V; 50V; 10A; 640W |