



Fagor Kore 900 Electric Pasta and Noodle Cooker - CP-E905

Quick Overview

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishes; screws hidden from view
- Wells integrated into the surface top, manufactured in 1.5 mm thick AISI-316L stainless steel
- Wells with 1/1 dimensions, capacity 40 liters. Accommodate different configurations of different-sized baskets
- Well filling using entrance electro valve with two-position switch: medium filling speed and high speed
- Draining of well using high temperature resistant mechanical ball valve with safety overflow
- Automatic safety system that breaks the circuit if the water runs out
- Drainer located at the front for the baskets to be rested on
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Electric models with AISI-304 stainless steel heating elements situated in the bottom of the well to heat the water directly
- Heating controls by the energy regulator

Description

Fagor Kore 900 Electric Pasta and Noodle Cooker CP-E905

Key Features

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishes; screws hidden from view
- Wells integrated into the surface top, manufactured in 1.5 mm thick AISI-316L stainless steel
- Wells with 1/1 dimensions, capacity 40 liters. Accommodate different configurations of different-sized baskets
- Well filling using entrance electro valve with two-position switch: medium filling speed and high speed
- Draining of well using high temperature resistant mechanical ball valve with safety overflow
- Automatic safety system that breaks the circuit if the water runs out
- Drainer located at the front for the baskets to be rested on
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Electric models with AISI-304 stainless steel heating elements situated in the bottom of the well to heat the water directly
- Heating controls by the energy regulator

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Knobs	2 knobs
Net Weight (Kg)	65
Width (mm)	400
Depth (mm)	930
Height (mm)	850
Packing Width (mm)	1022
Packing Depth (mm)	440
Packing Height (mm)	1255
Power	415V, 12kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice