



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Fagor M-E915BM Indirect Heating Boiling Pan | 150L | Electric | IPX5 | 22kW

Model / SKU: M-E915BM

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/8174/store/7/



Fagor Kore 900 Electric Indirect Heating Boiling Pan - M-E915BM

Quick Overview

- Capacity (L): 150
- 2 mm thick 304 S/S surface top
- Laser-cut joints and hidden screws
- Double-walled lid with front handle, with diagonal opening to 75°
- Well stamped into the surface top by robotic welding, manufactured in AISI-304 stainless steel, with the bottom of the well in AISI-316L stainless steel
- Well filling with hot or cold water by electro valve, activated with a single switch at the front panel
- 2" safety valve
- Robust and reliable 304 S/S drainage filter
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- IPX5 grade water protection
- Heating elements located in the lower part of the machine
- Heating controlled by energy regulator and pressure switch
- Bain-marie chamber around the well, with an automatic filling system when the machine is connected
- Automatic chamber level control with quadruple security: pressure switch to control the pressure in the chamber, overpressure security valve, thermostat to limit overheating in the chamber, and pressure gauge incorporated into the surface top
- Automatic flushing
- Heating at the bottom of the pan acts on the water in the surrounding chamber, meaning that the saturated steam generated at a temperature of 107 °C heats the bottom and sides of the well in a uniform manner
- The temperature reached is lower than that obtained with direct heating
- Stamped pan floor to avoid deformations
- Indicator light

Description

Fagor Kore 900 Electric Indirect Heating Boiling Pan - M-E915BM

Key Features

- Capacity (L): 150
- 2 mm thick 304 S/S surface top
- Laser-cut joints and hidden screws
- Double-walled lid with front handle, with diagonal opening to 75 °
- Well stamped into the surface top by robotic welding, manufactured in AISI-304 stainless steel, with the bottom of the well in AISI-316L stainless steel
- Well filled with hot or cold water by ean lectro valve, activated with a single switch at the front panel
- 2 " safety valve
- Robust and reliable 304 S/S drainage filter
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- IPX5 grade water protection
- Heating elements located in the lower part of the machine
- Heating controlled by energy regulator and pressure switch
- Bain-marie chamber around the well, with an automatic filling system when the machine is connected
- Automatic chamber level control with quadruple security: pressure switch to control the pressure in the chamber, overpressure security valve, thermostat to limit overheating in the chamber, and pressure gauge incorporated into the surface top
- Automatic flushing
- Heating at the bottom of the pan acts on the water in the surrounding chamber, meaning that the saturated steam generated at a temperature of 107 ° C heats the bottom and sides of the well in a uniform manner.
- The temperature reached is lower than that obtained with direct heating
- Stamped pan floor to avoid deformations
- Indicator light

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Knobs	2 knobs
Net Weight (Kg)	138
Width (mm)	800
Depth (mm)	930
Height (mm)	850
Packing Width (mm)	1022
Packing Depth (mm)	840
Packing Height (mm)	1255
Power	415V, 22kW/3~N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice