



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Fagor FTG-C9-05L Chrome Fry Top – NG, 1 Zone, 900 Series

Model / SKU: FTG-C9-05L

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://www.foodequipment.com.au/amfile/file/download/file/74/product/3515/>



900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-05 VL

DIMENSIONS		Article	Packed
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30
ELECTRICITY			
Not used			0,00

WATER

Not used

GAS			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

Certificate EQNET- CE

99AP56

GAS FRY-TOP, FTG9-05 VL

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.


Safety valve and thermocouple.

Fat collector under the grill.

Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-05 VR

DIMENSIONS		Article	Packed
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30
ELECTRICITY			
Not used			0,00

WATER

Not used

GAS			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

STEAM Not used

AIR Not used

Certificate EQNET- CE 99AP56

GAS FRY-TOP, FTG9-05 VR

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.


Safety valve and thermocouple.

Fat collector under the grill.

Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-05 L

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30
<u>ELECTRICITY</u>			
Not used			0,00

WATER

Not used

<u>GAS</u>			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 L

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-05 R

DIMENSIONS		Article	Packed
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30
ELECTRICITY			
Not used			0,00

WATER

Not used

GAS			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 VL

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
<u>ELECTRICITY</u>			
Not used			0,00
<u>WATER</u>			
Not used			
<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00
<u>STEAM</u>		Not used	
<u>AIR</u>		Not used	
<u>Certificate EQNET- CE</u>		99AP56	

GAS FRY-TOP, FTG9-10 VL

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.


Safety valves and thermocouples.

Fat collector under the grill.

Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 VR

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
<u>ELECTRICITY</u>			
Not used			0,00

WATER
Not used

<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00


STEAM Not used

AIR Not used

GAS FRY-TOP, FTG9-10 VR
Made of stainless steel.
Ribbed hot-plate. Surface area: 50 dm2.
Burners in stainless steel with pilot.
Piezoelectric burner ignition.
Safety valves and thermocouples.
Fat collector under the grill.
Power: 2 x 9,34 kW = 18,68 kW.
Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE 99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 V L+R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
<u>ELECTRICITY</u>			
Not used			0,00

WATER

Not used

<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 V L+R

Made of stainless steel.

2/3 smooth + 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valves and thermocouples.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 L

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
<u>ELECTRICITY</u>			
Not used			0,00

WATER

Not used

<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 L+R

DIMENSIONS

		Article	Packed
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 L+R

Made of stainless steel.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
<u>ELECTRICITY</u>			
Not used			0,00

WATER
Not used

<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00


STEAM Not used

AIR Not used

GAS FRY-TOP, FTG9-10 R
Made of stainless steel.
Ribbed hot-plate. Surface area: 50 dm2.
Burners in stainless steel with pilot.
Piezoelectric burner ignition.
Thermostat control of the hot-plate temperature 120 C° -310 C°.
Fat collector under the grill.
Power: 2 x 9,34 kW = 18,68 kW.
Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE 99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-05 L

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	80,00
Volumen	m3	0,12	0,30

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

<u>STEAM</u>	Not used
--------------	----------

<u>AIR</u>	Not used
------------	----------

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

GAS FRY-TOP, FTG/C9-05 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-05 R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		9,34
	Kcal/h		8.032,40
LPG	Consumption (kg/h)		0,74
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		0,95
	Pressure (g/cm2)		18,00

<u>STEAM</u>	Not used
--------------	----------

<u>AIR</u>	Not used
------------	----------

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

GAS FRY-TOP, FTG/C9-05 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-10 L

DIMENSIONS		Article	Packed
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57
ELECTRICITY			
Not used			0,00
WATER			
Not used			
GAS			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00
STEAM		Not used	
AIR		Not used	

GAS FRY-TOP, FTG/C9-10 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-10 L+R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00

<u>STEAM</u>	Not used
--------------	----------

<u>AIR</u>	Not used
------------	----------

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

GAS FRY-TOP, FTG/C9-10 L+R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. 2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-10 R

DIMENSIONS		Article	Packed
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY			
Not used			0,00

WATER	
Not used	

GAS			
Power	KW		18,68
	Kcal/h		16.064,80
LPG	Consumption (kg/h)		1,48
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		1,90
	Pressure (g/cm2)		18,00

STEAM	Not used
-------	----------

AIR	Not used
-----	----------

Certificate EQNET- CE	99AP56
-----------------------	--------

GAS FRY-TOP, FTG/C9-10 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-05 L

DIMENSIONS		Article	Packed
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29
ELECTRICITY			
Electric power		KW	6,00
230V -1+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE9-05 L

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 Cº -310 Cº.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-05 R

DIMENSIONS		Article	Packed
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29
ELECTRICITY			
Electric power		KW	6,00
230V - I+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE9-05 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V -1+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-10 L+R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V -1+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 L+R

Made of stainless steel.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V -1+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE/C9-05 L

DIMENSIONS		Article	Packed
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29
ELECTRICITY			
Electric power		KW	6,00
230V - I+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE/C9-05 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Smooth hot-plate. Surface area: 24 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE/C9-05 R

DIMENSIONS		Article	Packed
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29
ELECTRICITY			
Electric power		KW	6,00
230V - I+N			2x4+T - 32 A
230V - III			3x2,5+T - 20 A
400V - III+N			4x1,5+T - 16 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE/C9-05 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Ribbed hot-plate. Surface area: 24 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE/C9-10 L

DIMENSIONS		Article	Packed
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57
ELECTRICITY			
Electric power		KW	12,00
230V -1+N		2x10+T	- 100 A
230V - III		3x6+T	- 63 A
400V - III+N		4x2,5+T	- 32 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE/C9-10 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Smooth hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE/C9-10 L+R

DIMENSIONS		Article	Packed
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57
ELECTRICITY			
<u>Electric power</u>		KW	12,00
230V -1+N		2x10+T	- 100 A
230V - III		3x6+T	- 63 A
400V - III+N		4x2,5+T	- 32 A
WATER			
Not used			
GAS			
Not used			
STEAM		Not used	
AIR		Not used	

ELECTRIC FRY-TOP, FTE/C9-10 L+R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE/C9-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V -1+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-10 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG9-11 L

DIMENSIONS		Article	Packed
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07
ELECTRICITY			
Not used			0,00
WATER			
Not used			
GAS			
Power	KW		27,28
	Kcal/h		23.460,80
LPG	Consumption (kg/h)		2,26
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,87
	Pressure (g/cm2)		18,00
STEAM		Not used	
AIR		Not used	

GAS FRY-TOP WITH OVEN, FTG9-11 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG9-11 L+R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		27,28
	Kcal/h		23.460,80
LPG	Consumption (kg/h)		2,26
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,87
	Pressure (g/cm2)		18,00

<u>STEAM</u>	
	Not used

<u>AIR</u>	
	Not used

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

GAS FRY-TOP WITH OVEN, FTG9-11 L+R

Made of stainless steel.

2/3 Smooth + 1/3 Ribbed hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.


Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG9-11 R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		27,28
	Kcal/h		23.460,80
LPG	Consumption (kg/h)		2,26
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,87
	Pressure (g/cm2)		18,00

<u>STEAM</u>	
	Not used

<u>AIR</u>	
	Not used

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

GAS FRY-TOP WITH OVEN, FTG9-11 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.


Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG/C9-11 L

DIMENSIONS

		Article	Packed
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG/C9-11 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG/C9-11 L+R

DIMENSIONS		Article	Packed
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY			
Not used			0,00

WATER			
Not used			

GAS			
Power	KW		27,28
	Kcal/h		23.460,80
LPG	Consumption (kg/h)		2,26
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,87
	Pressure (g/cm2)		18,00

STEAM			
	Not used		

AIR			
	Not used		

Certificate EQNET- CE		99AP56
-----------------------	--	--------

GAS FRY-TOP WITH OVEN, FTG/C9-11 L+R

Made of stainless steel.

2/3 Smooth + 1/3 Ribbed hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.


Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP WITH OVEN, FTG/C9-11 R

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

<u>ELECTRICITY</u>			
Not used			0,00

<u>WATER</u>	
Not used	

<u>GAS</u>			
Power	KW		27,28
	Kcal/h		23.460,80
LPG	Consumption (kg/h)		2,26
	Pressure (g/cm2)		37,00
Natural Gas	Consumption (m3/h)		2,87
	Pressure (g/cm2)		18,00

<u>STEAM</u>	
Not used	

<u>AIR</u>	
Not used	

GAS FRY-TOP WITH OVEN, FTG/C9-11 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

<u>Certificate EQNET- CE</u>	99AP56
------------------------------	--------

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual

