



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Bonvue HTR120N Chilled Counter-Top Food Display – 695 mm

Model / SKU: HTR120N


KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/5131/store/7/



Bonvue Chilled Counter-Top Food Display - HTR120N

Quick Overview

- Gross Volume: 115L
- Net Volume: 78L
- Max Ambient Temperature: 32°C;
- Temperature Range: 3 to 8 ° C
- Sliding Rear Doors
- CFC-free refrigerant and foam
- A ventilated refrigeration compartment gives better air circulation
- Auto defrosting
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Curved glass food display
- Fan-forced air flow
- LED lamp
- HC refrigerant
- 2 adjustable Shelving
- Refrigeration Unit Is Fully Self-Contained In The Base (No Well Cut-Out Is Required)
- Internal dimension: 663 x 498 x 384 mm
- Shelf dimension: One 642 x 372 + One 642 x 408 mm
- Front glass: Tempered double-glazed glass

Description

Bonvue Chilled Counter-Top Food Display - HTR120N

The standard chilled display from the renowned commercial refrigeration brand, Bonvue, contains decent power.

One of Bonvue 's standardised benchtop displays, this piece works wonders in keeping your meals and ingredients chilled and made ready for serving.

Encased with a picturesque curved glass display, this unit is built with a strong stainless-steel base, digital temp controller, LED

display, and a perfected ventilated refrigeration system.

Three Levels Of Display In A Stainless Steel And Glass Cabinet

Key Features

- Gross Volume: 115L
- Net Volume: 78L
- Max Ambient Temperature: 32
- Temperature Range: +3 to +8 ° C
- Sliding Rear Doors
- CFC-free refrigerant and foam
- A ventilated refrigeration compartment gives better air circulation
- Auto defrosting
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Curved glass food display
- FFan-forcedairflow
- LED lamp
- HC refrigerant
- 2 adjustable Shelving
- Refrigeration Unit Is Fully Self-Contained In The Base (No Well Cut-Out Is Required)
- Internal dimension: 663 x 498 x 384 mm
- Shelf dimension: One 642 x 372 + One 642 x 408 mm
- Front glass: Tempered double-glazed glass

1 Year Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Sliding Doors
Body	Stainless Steel
Gross Volume	115L
Net Volume	78L
Max Ambient Temperature	32
Temperature Range	+3 to +8 ° C
Total Energy Consumption	4.054 (kWh/24h)
Net Weight (Kg)	64
Width (mm)	695
Depth (mm)	498
Height (mm)	384
Packing Width (mm)	753
Packing Depth (mm)	624
Packing Height (mm)	710
Power	240V; 160W / 10A
Warranty	1 Year Parts and Labour