



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Airex AXR.SW.1025 Sandwich Prep Bench – 1 Door, 1025mm

Model / SKU: AXR.SW.1025


KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

axr.sw.1025 c6 datasheet

SKU: AXR.SW.1025

Distributed by KW Commercial - kwcommercial.com.au

Manufacturer documentation - (c) Airex

Retrieved: 2026-07-08

<https://www.kwcommercial.com.au/product/airex-axr-sw-1025-sandwich-prep-bench>

Product Information

- Refrigerated GN 1/3 size service well with cold air blowing above and below ingredient pans. Includes under counter refrigerated storage below
- Sliding perspex lids for blown well
- Designed to operate at ambient temperatures up to 40°C with lid on, 32°C with lid off
- Digital temperature display and control
- Designed to operate between 2°C – 5°C
- Full-length, back mounted, coated evaporator coil for uniformed cooling across the entire well
- Removable filter for easy cleaning
- Fully self-contained
- Supplied on standard and lockable castors for ease of cleaning
- Cutting board, 9 x 1/3 GN Pans (100mm deep) supplied as standard
- 2 and 3 door models also available



Designed & Engineered in Australia to meet Australian Standards
24 Months on-site parts and labour warranty

Specifications

Model	AXR.SW.1025
W x D x H (mm)	1025 x 843 x 915
Weight	112kg
Packed Dimensions (mm)	1075 x 880 x 965
Packed Weight	125kg
Capacity	5 x 1/3GN
Operation	2°C - 5°C
Refrigerant	R290
Max Ambient	40°C
Total Connected Load	0.59kW
Electrical Connection	1Ø+N+E 230VAC / 50Hz 10A plug & lead

Legend

A Electrical Connection

Accessories

Frameless Glass Gantry	AXR.SW.1025.GAN
Gantry Dimensions (mm)	1007 x 500 x 450

