



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Sammic PP-6+ Commercial potato peeler – 400 W, aluminium

Model / SKU: PP-6+


KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://www.sammic.com.au/wp-content/uploads/2025/brochures/PP-6.pdf>



Gamma aluminium **PP / PPC**



POTATO PEELERS



Commercial potato peelers

To peel potatoes, carrots and other similar foods quickly and safely.

- Made of highly resistant **aluminium**.
- **Abrasive** peeling: abrasive lined chamber walls and base plate.
- Integral control panel complete with on/off push buttons and a 0-6 minute timer.
- **Orientable** cylinder.
- PPC: equipped with an attachment drive to power accessories.

Vegetable preparation attachment CR-143	Potato masher attachment P-132	Meat mincer attachment HM-71
		
To cut all types of greens and vegetables and grate cheese, bread, chocolate, etc.	Allows a homogeneous puree ideal for boiled potato, boiled beans, carrot, fruit and vegetables	For chopping small amounts of meat in the best hygiene conditions

- **Optional equipment:**
 - Soportes
 - Filtros anti-espuma para las peladuras.





Part of a complete solution :

SAMMIC FRENCH FRY SYSTEM



Optimization process for the production and storage of fresh french fries. French fries will stay perfectly fresh for 8 to 9 days once peeled, cut, vacuum packed and chilled in one process.

• PEEL •



• CUT •



• VACUUM PACK •





FEATURES	PP-6	PPC-6	PP-12	PPC-12
Selection guide				
Covers (from / to)	30-150	30-150	60-200	60-200
Features				
Capacity per load	6 Kg	6 Kg	12 Kg	12 Kg
Production /hour (max)	150 kg	150 kg	270 kg	270 kg
Timer	0 - 6'	0 - 6'	0 - 6'	0 - 6'
Loading				
Single Phase	400	550	400	550
Three phase	370	550	370	550
Attachment drive	No	Yes	No	Yes
External dimensions				
External dimensions (WxDxH)	395 x 700 x 433mm	395 x 700 x 433mm	395 x 700 x 503mm	395 x 700 x 503mm
External dimensions with stand	411 x 700 x 945mm	411 x 700 x 945mm	411 x 700 x 1015mm	411 x 700 x 1015mm
Net weight	37 Kg	37 Kg	38 Kg	38 Kg

