



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

TurboChef SPTC.i3 i3 Ventless Rapid Cook Oven – High Throughput

Model / SKU: SPTC.i3

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

sptc.i3 a2 datasheet

SKU: SPTC.i3

Distributed by KW Commercial - kwcommercial.com.au

Manufacturer documentation - (c) TurboChef

Retrieved: 2026-07-08

<https://www.kwcommercial.com.au/product/turbochef-sptc-i39039-rapid-cook-oven-air-filter>

Product Information

- 7" intuitive capacitive touch screen with one-touch controls and icons, featuring durable tempered glass
- Smart menu system store up to 200 recipes with customisable menu settings via IoT, USB, or manual entry
- Flash firmware updates and programmable via USB
- Single or multiple-temperature interface
- Integral recirculating catalytic converter for ventless operation
- Independently-controlled top and bottom dual motors for recirculating impingement airflow
- Self-diagnostics for monitoring oven components and performance
- Patented Top-launched microwave system with stirrer to help ensure even distribution of air and microwave
- Unique microwave system that allows for use of all metal pans and cookware
- Fully insulated cook chamber
- Top and bottom jetplates
- External air filtration
- Rubber seal for surface mounting
- i3 units can be stacked (requires stacking kit, sold separately)

- **12-month warranty (Terms and conditions apply)**

Included Accessories

- 1 Aluminum Paddle
- 1 Bottle Oven Cleaner
- 1 Bottle Oven Guard
- 2 Trigger Sprayers
- 2 PTFE Baskets

Specifications

Model	SPTC.i3
W x D x H (mm)	622 x 794 x 540
Weight	111kg
Chamber W x D x H (mm)	493 x 375 x 175
Volume	32.3 Litres
Total Connected Load	9.5kW (20A circuit*)
Electrical Connection	3Ø + N + E 400VAC / 50Hz Clipsal, 5-pin, 20A plug and lead fitted (1.8m)

*This oven requires a D type circuit breaker for all installations.

Shipping	Box: 940 x 610 x 940 / 77kg Crate: 965 x 660 x 965 / 109kg
-----------------	---

Legend

- A** Electrical Connection
- B** USB Input

