



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Airex AXR.UCGN.3 Undercounter Refrigerator – 3 Solid Door 1/1GN

Model / SKU: AXR.UCGN.3

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

axr.ucgn.3 c2 datasheet

SKU: AXR.UCGN.3

Distributed by KW Commercial - kwcommercial.com.au

Manufacturer documentation - (c) Airex

Retrieved: 2026-07-08

<https://www.kwcommercial.com.au/product/airex-axr-ucgn-3g-triple-glass-undercounter-fridge-1-1gn>

Product Information


- Monoblock refrigeration system, for improved performance and ease of servicing
- Adjustable digital temperature controller (0°C - 6°C)
- Unique fan forced ducted cooling for uniformed performance throughout the entire refrigerator
- Protective coating on refrigeration coil to help prevent corrosion
- Environmentally friendly R290 Hydrocarbon refrigerant
- Efficient LED lighting for increased product visibility
- Stainless Steel worktop as standard, 840mm finish height. (Optional 900mm working height model available)
- 1/1GN shelf configuration with adjustable runners (2 shelves per door)
- 60mm CFC free polyurethane insulation
- Efficient and hygienic cleaning made easy with an innovative internal design
- High quality components including highly efficient compressors and EC fans
- Self-closing, lockable doors
- Removable filter for easy cleaning
- Equipped standard with lockable castors designed for heavy-duty use
- 2 and 4 door models also available, with glass or solid doors



Designed & Engineered in Australia to meet Australian Standards
24 Months on-site parts and labour warranty

Specifications

Model	AXR.UCGN.3
W x D x H (mm)	1795 x 700 x 840
Weight	122kg
Packed Dimensions (mm)	1825 x 730 x 880
Packed Weight	146kg
Net Capacity	276 Litres
Operation	0°C - 6°C
Refrigerant	R290
Climate Class	4M1
Energy Consumption	3.74kWh/24hr
Max Ambient	40°C
Total Connected Load	0.38kW
Electrical Connection	1Ø+N+E 230VAC / 50Hz 10A plug & lead



Legend

A Electrical Connection

Accessories

Shelf Kit - AXR.UCGN.SHELFKIT
 1/1GN shelf with runners