



Fagor iNova Concept Pass-Through Dishwasher - WHC-502TBD

Quick Overview

- Hourly production: 40 baskets/hour
- Clearance (max ware height): 450mm
- Electro-Mechanical Controls with Robust Back-Lit Pushbuttons
- Wash cycles: 55°/75°/120°
- Stainless steel construction
- Duo-KLIP Wash/rinse arms
- Wash pump, 750W each
- Drain pump: 100W drainage cycle
- Wash Tank with 3 kW heating power
- Tank capacity: 33 litres
- Boiler heating power: 6 kW
- Boiler capacity: 9 litres
- Water consumption: 2.2 litres/cycle
- Thermostatic temperature control: washing at 60°; and rinsing at 85°;
- Two-digit LED displays
- Hydraulic rinse aid dispenser
- Dual-flow wash pump with soft-start
- Double-stage filtration system
- Dual-flow wash pumps
- Volumetric rinse
- A magnetic micro switch to stop the cycle in case of accidental opening of the hood.
- Adjustable legs
- Supplied with 1 glass basket, 1 plate basket, and 1 cutlery container
- Watermark approved
- Temperature control by electronic probes
- i-ERROR DIAGNOSIS: Error identification on screen
- Drain pump
- Hydraulic rinse aid dispenser and Peristaltic detergent dispenser

Â

Description

Fagor iNova Concept Pass-Through Dishwasher - WHC-502TBD

iNova Concept high-performance hood-type pass-through dishwasher designed for fast, efficient commercial kitchens. Suitable for a 500x500 basket with mains pressure, LED displays, drain pump and detergent dispenser.

Key Features

- Hourly production: 40 baskets/hour
- Clearance (max ware height): 450mm
- Electro-Mechanical Controls with Robust Back-Lit Pushbuttons
- Wash cycles: 55 " / 75 " / 120
- Stainless steel construction
- Duo-KLIP Wash/rinse arms
- Wash pump, 750W each
- Drain pump: 100W drainage cycle
- Wash Tank with 3 kW heating power
- Tank capacity: 33 litres
- Boiler heating power: 6 kW
- Boiler capacity: 9 litres
- Water consumption: 2.2 litres/cycle
- Thermostatic temperature control: washing at 60 °C and rinsing at 85 °C
- Two-digit LED displays
- Hydraulic rinse aid dispenser
- Dual-flow wash pump with soft-start
- Double-stage filtration system
- Dual-flow wash pumps
- Volumetric rinse
- A magnetic micro switch to stop the cycle in case of accidental opening of the hood.
- Adjustable legs
- Supplied with 1 glass basket, 1 plate basket, and 1 cutlery container
- Watermark approved
- Temperature control by electronic probes
- i-ERROR DIAGNOSIS: Error identification on screen
- Drain pump
- Hydraulic rinse aid dispenser and Peristaltic detergent dispenser

2 Years Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	98
Width (mm)	630
Depth (mm)	750
Height (mm)	1480
Packing Width (mm)	765
Packing Depth (mm)	905
Packing Height (mm)	1610
Power	215V, 9.75kW/3-N
Warranty	2 Years Parts and Labour Warranty