



Fagor iNova Heated Recovery Pass-Through Dishwasher - WHC-502TRCBD

Quick Overview

- Energy Efficiency: Reuses waste heat to preheat incoming water, reducing energy use.
- Lower Operating Costs: Cuts down on energy bills through efficient heat recovery.
- Improved Working Environment: Minimises hot steam release, keeping the kitchen cooler and more comfortable.
- No Need for Direct Exhaust Ventilation: Eliminates the requirement for an external exhaust hood, saving on installation costs.
- Hourly production: 40 baskets/ hour
- Clearance (max ware height): 450mm
- Electronic control
- Wash cycles: 55°/75°/120°
- Double rotating wash and rinse systems, made of AISI-304 stainless steel
- Wash pump, 750W each
- Drain pump: 100W drainage cycle
- Tank with 3 kW heating power
- Tank capacity: 33 litres
- Water consumption: 2.2 litres/cycle
- Thermostatic temperature control: washing at 60°; and rinsing at 85°;
- Two-digit LED displays
- Hydraulic rinse aid dispenser
- Dual-flow wash pump with soft-start
- Double-stage filtration system
- Dual-flow wash pumps
- A magnetic micro switch to stop the cycle in case of accidental opening of the hood
- Adjustable legs
- Supplied with 1 dish basket, 1 glass basket and 1 cutlery container
- Watermark approved
- Can be converted to single-phase
- Precision of working temperatures
- Temperature control by electronic probes
- Configurable control
- i-ERROR DIAGNOSIS: Error identification on screen
- Basket: 500x500
- Drain pump

Description

SEED-certified ventless installation – no external kitchen exhaust hood required.*

Hood-type dishwasher concept range with a heat recovery system for a 500x500 basket with mains pressure, LED displays, drain pump, and detergent dispenser

Key Features

- Energy Efficiency: Reuses waste heat to preheat incoming water, reducing energy use.
- Lower Operating Costs: Cuts down on energy bills through efficient heat recovery.
- Improved Working Environment: Minimises hot steam release, keeping the kitchen cooler and more comfortable.
- No Need for Direct Exhaust Ventilation: Eliminates the requirement for an external exhaust hood, saving on installation costs.
- Hourly production: 40 baskets/ hour
- Clearance (max ware height): 450mm
- Electronic control
- Wash cycles: 55 " / 75 " / 120
- Double rotating wash and rinse systems, made of AISI-304 stainless steel
- Wash pump, 750W each
- Drain pump: 100W drainage cycle
- Tank with 3 kW heating power
- Tank capacity: 33 litres
- Water consumption: 2.2 litres/cycle
- Thermostatic temperature control: washing at 60 °C and rinsing at 85 °C
- Two-digit LED displays
- Hydraulic rinse aid dispenser
- Dual-flow wash pump with soft-start
- Double-stage filtration system
- Dual-flow wash pumps
- A magnetic micro switch to stop the cycle in case of accidental opening of the hood
- Adjustable legs
- Supplied with 1 dish basket, 1 glass basket, and 1 cutlery container
- Watermark approved
- Can be converted to single-phase
- Precision of working temperatures
- Temperature control by electronic probes
- Configurable control
- I-ERROR DIAGNOSIS: Error identification on screen
- Basket: 500x500
- Drain pump

*Subject to compliant background ventilation, site mechanical approval, Fagor commissioning and maintenance requirements.

2-Year Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	117
Width (mm)	630
Depth (mm)	750
Height (mm)	1975
Packing Width (mm)	765
Packing Depth (mm)	905
Packing Height (mm)	1770
Power	415V, 9.75kW/3-N
Warranty	2 Years Parts and Labour Warranty