



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Bonvue CL900-3S Cold Display Cabinet – 900mm, 3 Shelves

Model / SKU: CL900-3S

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://www.foodequipment.com.au/md_productpdf/index/generate/product/9354/store/7/



Bonvue Elite Cold Displays with 3 shelves - CL900-3S

Quick Overview

- Height-adjustable glass shelves for custom layout. Each shelf has a load capacity of 20kg
- Heated front glass to reduce fogging
- Crystal-Clear Product Visibility
- Bright LED strip lighting above and below each shelf for full product exposure, day or night
- Digital controller for precise temperature management
- Auto-defrost with evaporating condensate—no manual drainage, less hassle
- Full 360° double-tempered glass—sturdy, safe, and spotless views from all sides
- Engineered for the Australian environment
- Smooth sliding rear doors for easy access
- Dual-brake castors for stability and manoeuvrability
- Natural and eco-friendly refrigerant—R600a

Description

Bonvue Elite Cold Displays with 3 shelves - CL900-3S

Key Features

- Height-adjustable glass shelves for custom layout. Each shelf has a load capacity of 20kg
- Heated front glass to reduce fogging
- Crystal-Clear Product Visibility
- Bright LED strip lighting above and below each shelf for full product exposure, day or night
- Digital controller for precise temperature management
- Auto-defrost with evaporating condensate—no manual drainage, less hassle
- Full 360° double-tempered glass—sturdy, safe, and spotless views from all sides
- Engineered for the Australian environment
- Smooth sliding rear doors for easy access

- Dual-brake castors for stability and manoeuvrability
- Natural and eco-friendly refrigerant

1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice

Your Shipping Specifications

Product Condition	New
Door Type	Sliding Doors
Body	Stainless Steel
Gross Volume	485L
Max Ambient Temperature	30°C, 55%RH
Temperature Range	+2 to +8°C
Form Factor	Display
Net Weight (Kg)	156
Width (mm)	900
Depth (mm)	705
Height (mm)	1350
Packing Width (mm)	970
Packing Depth (mm)	770
Packing Height (mm)	1485
Power	240V, 670W/10A
Warranty	1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice