



Fagor iNova Concept Front Loading Dishwasher - WUC-502TBD

Quick Overview

- Hourly production: 40 baskets/hour
- Clearance (max ware height): 385mm
- Electronic control
- Wash cycles: 55°/75°/120°;
- Stainless steel construction
- Wash pump, 680W each
- Rinse pump: 130W power
- Drain pump: 40W drainage cycle
- Tank with 2.8 kW heating power
- Tank capacity: 20 litres
- Boiler heating power: 2.8kW
- Boiler capacity: 7 litres
- Water consumption: 2.2 litres/ cycle
- Thermostatic temperature control: washing at 60°; and rinsing at 85°;
- Two-digit LED displays
- Soundproofed and heat-resistant double-skin door.
- A magnetic micro switch to stop the cycle in case of accidental opening of the door.
- Triple-stage filtering system
- Dual-flow wash pumps
- Duo-KLIP Wash/rinse arms
- Volumetric rinse
- Adjustable legs
- Temperature control by electronic probes.
- i-ERROR DIAGNOSIS Error identification on screen
- Indications on the screen
- Drain pump
- Hydraulic rinse aid dispenser and Peristaltic detergent dispenser
- Supplied with 1 glass basket, 1 plate basket, and 1 cutlery basket containers
- Watermark approved

Description

Fagor iNova Concept Front Loading Dishwasher - WUC-502TBD

Front-loading dishwasher concept range for a 500x500 basket with mains pressure, LED displays, drain pump and detergent dispenser.

Key Features

- Hourly production: 40 baskets/hour

- Clearance (max ware height): 385mm
- Electronic control
- Wash cycles: 55 " /75 " /120 "
- Stainless steel construction
- Wash pump, 680W each
- Rinse pump: 130W power
- Drain pump: 40W drainage cycle
- Tank with 2.8 kW heating power
- Tank capacity: 20 litres
- Boiler heating power: 2.8kW
- Boiler capacity: 7 litres
- Water consumption: 2.2 litres/ cycle
- Thermostatic temperature control: washing at 60 °C and rinsing at 85 °C
- Two-digit LED displays
- Soundproofed and heat-resistant double-skin door.
- A magnetic micro switch to stop the cycle in case of accidental opening of the door.
- Triple-stage filtering system
- Dual-flow wash pumps
- Duo-KLIP Wash/rinse arms
- Volumetric rinse
- Adjustable legs
- Temperature control by electronic probes.
- i-ERROR DIAGNOSIS Error identification on screen
- Indications on the screen
- Drain pump
- Hydraulic rinse aid dispenser and Peristaltic detergent dispenser
- Supplied with 1 glass basket, 1 plate basket, and 1 cutlery basket containers
- Watermark approved

2 Years Parts and Labour

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	51
Width (mm)	576
Depth (mm)	605
Height (mm)	835
Packing Width (mm)	600
Packing Depth (mm)	745
Packing Height (mm)	1030
Power	240V, 3,48kW/15A
Warranty	2 Years Parts and Labour