



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Bezzera BZMODAPID2B Moda PID 2-Group Espresso Machine – 11L, Black

Model / SKU: BZMODAPID2B

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://www.foodequipment.com.au/amfile/file/download/file/4388/product/9427/>



Pre-Installation Checklist

2 GROUP MACHINE

	Plumber	Electrician	Shopfitter/ Builder	Coffee Technician
☐ 20amp 3 pin outlet - within 1000mm of machine	✗	✓	✓	✗
☐ Mains pressure 3-7 bars - Cold water tap with 350kpa Pressure limiting valve (350kpa PLV) with 10mm male connection - within 1000mm	✓	✗	✓	✗
☐ ≥50mm S-trap waste point under the machine - within 1000mm	✓	✗	✓	✗
☐ ≥50mm hole saw bench - directly under where machine position	✗	✗	✓	✗



Book your Installation with a Coffee Technician – visit [bzau.com.au](https://www.bzau.com.au)


The above information and advice is general in nature. If you are unsure of any part of the installation, speak to a registered Bezzera Australia Coffee Technician today.




Pre-Installation Checklist

3 GROUP MACHINE


	Plumber	Electrician	Shopfitter/ Builder	Coffee Technician
☐ Mains pressure 3-7 bars - Cold water tap with 350kpa Pressure limiting valve (350kpa PLV) with 10mm male connection - within 1000mm	✓	✗	✓	✗
☐ ≥50mm S-trap waste point under the machine - within 1000mm	✓	✗	✓	✗
☐ ≥50mm hole saw bench - directly under where machine position	✗	✗	✓	✗
☐ 32amp 3 pin outlet - within 1000mm of machine	✗	✓	✓	✗
☐ 32amp plug on coffee machine	✗	✓	✓	✗
OR				
☐ 32amp hard wired - within 1000mm of machine	✗	✓	✓	✗




V380-415/3+N
THREE-PHASE
삼상 별
CONNECTION WITH
NEUTRAL
중성과의 연결



V220-240/3
THREE-PHASE
삼상 델타
CONNECTION
연결



V220-240/2
SINGLE-PHASE
단일 위상
CONNECTION
연결



V220-240/2
SINGLE-PHASE
단일 위상
CONNECTION
연결

(0) Blu (Neutral) (0) 블루 (우중충한)	(0) Blu (Neutral) (0) 블루 (우중충한)	(0) Blu (Neutral) (0) 블루 (우중충한)	(0) Blu (Neutral) (0) 블루 (우중충한) (0) White (neutral for USA)
(1) Brown (1) 갈색	(1) Brown + (3) Grey (1) 갈색 + (3) 회색	(1) Brown + (2) Black + (3) Grey (1) 갈색 + (2) 검은 (3) 회색	(1) Brown (1) 갈색 + (1) Black for USA
(2) Black, (2) 검은	(2) Black, (2) 검은		
(3) Grey, (3) 회색			
(3P+N+T)	(3P+T)	(1P+N+T)	(1P+N+T)
380-415 Vac; 50-60 Hz	220-240 Vac; 50-60 Hz	220-240 Vac; 50-60 Hz	220-240 Vac; 50-60 Hz