



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Blue Seal Evolution Series IN54R3 - 900mm Induction Range Convection Oven

Model / SKU: IN54R3

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/IN54R_AN.pdf

INDUCTION RANGE CONVECTION OVEN 900mm

IN54R3 - GN 2/1 Electric Convection Oven with 4 x 3.5kW Round Induction

IN54R5 - GN 2/1 Electric Convection Oven with 4 x 5.0kW Round Induction

IN54R5F - GN 2/1 Electric Convection Oven with 2 x 5.0kW Round Induction and 2 x 5.0kW Full Area Induction




- Heavy-duty construction
- Four Induction zones
- R3 4 x 3.5kW Round Induction zones
- R5 4 x 5.0kW Round Induction zones
- R5F 2 x 5.0kW Round / 2 x 5kW Full Area Induction zones
- Automatic pan detection
- GN 2/1 6.1kW electric convection oven
- Dual oven circulation fans
- Drop down door
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular

Induction Zones

R3 - 4 x 3.5kW Round Induction

R5 - 4 x 5kW Round Induction

R5F - 2 x 5kW Round Induction / 2 x 5.0kW Full Area induction



IN54R3/R5

IN54R5F

Overall Construction

- Galvanized steel chassis
- Welded hob with 2.0mm 304 stainless steel top
- Splashback and hob sides 1.2mm 304 stainless steel
- Front panels and oven sides 0.9mm 304 stainless steel
- Vitreous enamelled control panel
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear

Cooktop

- Two 6mm thick ceramic glass 375mm x 650mm each
- Induction air cooling with front access air filter
- Fan cooled induction cooktop oven heat protection with front exhaust

Oven

- Fully welded and vitreous enamelled oven liner
- GN 2/1 capacity with 5 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Vitreous enamelled removable oven spill tray
- 6.0kW heating elements
- 2 fan motors
- Drop down door
- 0.9mm 304 stainless steel door outer
- 1.0mm vitreous enamelled door inner
- 38mm high density fibreglass insulated
- Supplied with two chrome wire oven racks

Controls

Induction Cooktop

- Variable power controls for each induction zone
- Heating ON indicator lights with pan detection indication
- Error mode indicator

Oven

- 50-320°C thermostatic control
- Indicator lights for power and heating
- Oven fans and heating automatic off when door open

Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Fully sealed cooking surface
- Removable for cleaning cooling air filter
- Removable for cleaning exhaust screen
- Removable oven racking and spill tray
- Easy clean vitreous enamel oven and door inner
- Access to all service parts from front of unit

INDUCTION RANGE CONVECTION OVEN 900mm

IN54R3 - GN 2/1 Electric Convection Oven with 4 x 3.5kW Round Induction

IN54R5 - GN 2/1 Electric Convection Oven with 4 x 5.0kW Round Induction

IN54R5F - GN 2/1 Electric Convection Oven with 2 x 5.0kW Round Induction and 2 x 5.0kW Full Area Induction

Specifications

Cooktop

IN54R3

4 x 3.5kW Ø 270mm Round Induction zones

IN54R5

4 x 5.0kW Ø 270mm Round Induction zones

IN54R5F

2 x 5.0kW Ø 270mm Round Induction (LH)

2 x 5.0kW Full Area Induction zones (RH)

Oven

2 x 2kW oven fan elements

1 x 2kW oven bottom element

2 x oven circulation fan motors

Oven dimensions

Width 665mm

Depth 560mm

Height 350mm

Rack size 655mm x 530mm

Rack positions 5

Electrical requirements

IN54R3

20.1kW, 400-415V, 50/60Hz, 3P+N+E

28.5A / phase

IN54R5

26.1kW, 400-415V, 50/60Hz, 3P+N+E

36.3A / phase

IN54R5F

26.1kW, 400-415V, 50/60Hz, 3P+N+E

36.3A / phase

Electrical connection

130mm from RH side, 32mm from rear,
and 318mm from floor

Dimensions

Width 900mm

Depth 812mm

Height 915mm

Incl. splashback 1085mm

Nett weight

168.5kg

Packing data

1.03m3, 235kg

Width 945mm

Depth 865mm

Height 1255mm



Options

Adjustable feet at rear


Castors

Plinth mounting


IN54



IN54R3, IN54R5



IN54R5F



moffat.com.au

moffat.co.nz

Australia

moffat.com.au

Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au

New South Wales
Telephone +612-8833 4111
nswsales@moffat.com.au

South Australia
Telephone +613-9518 3888
vsales@moffat.com.au

Queensland
Telephone +617-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone +618-9413 2400
wasales@moffat.com.au

New Zealand

moffat.co.nz

Moffat Limited

Rolleston
45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz

Auckland
Telephone +64 9-574 3150
sales@moffat.co.nz



In line with policy to continually develop
and improve its products, Moffat Limited
reserves the right to change specifications
and design without notice.

© Copyright Moffat Ltd
AN.BSE.01.23

an Ali Group Company



The Spirit of Excellence