



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Waldorf Bold INB8100W3-CD - 450mm Induction Wok - Cabinet Base

Model / SKU: INB8100W3-CD

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/INLB810_an.pdf

Waldorf Bold

Induction Wok 450mm

INLB8100W3-B, INLB8100W3-LS, INLB8100W3-CD, INLB8100W5-B, INLB8100W5-LS, INLB8100W5-CD



INLB8100W3(5)-CD

- Heavy-duty construction
- 300mm round induction wok
- 3.5kW or 5kW models
- Automatic pan detection switches induction off when wok pan removed
- 3 models of base unit
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular

OVERALL CONSTRUCTION

COOKTOP

- Welded hob with 2.0mm 304 stainless steel hob top
- Splashback and side panels 1.2mm 304 stainless steel
- Front panels 0.9mm 304 stainless steel
- 6mm thick ceramic glass wok hole

BENCH MOUNT (supplied as – B model)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet
- Adjustable height 80mm – 105mm

LEG STAND (supplied as – LS model)

- Fully modular for matched suite finish
- Framed top for connection to Cooktop
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with four adjustable feet
- Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- Quick assembly design

CABINET BASE WITH DOOR (supplied as – CD model)

- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- Double skin door with enamelled exterior panel
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with four adjustable feet

CONTROLS

- Large easy use control knob
- Variable power control
- Heating ON indicator light including pan detection indication
- Error mode indicator light

CLEANING AND SERVICING

- All models with easy clean stainless steel external finish
- Fully sealed cooking surface
- Removable full stainless steel air intake filter (induction cooling)
- Front service access

Induction Options

- W3 - 3.5kW single phase
- W5 - 5kW three phase

Series Options

- INLB - Low back models
- INB - 215mm splashback option

Induction Wok 450mm

INLB8100W3-B, INLB8100W3-LS, INLB8100W3-CD, INLB8100W5-B,
INLB8100W5-LS, INLB8100W5-CD



moffat.com.au
moffat.co.nz

Australia
moffat.com.au

Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone +613-9518 3888
Facsimile +613-9518 3833
vsales@moffat.com.au
New South Wales
Telephone +612-8833 4111
nswsales@moffat.com.au

South Australia
Telephone +613-9518 3888
vsales@moffat.com.au

Queensland
Telephone +617-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone +618-9413 2400
wasales@moffat.com.au

New Zealand
moffat.co.nz

Moffat Limited

Rolleston
45 Illinois Drive
Izone Business Hub
Rolleston 7675
Telephone +64 3-983 6600
Facsimile +64 3-983 6660
sales@moffat.co.nz
Auckland
Telephone +64 9-574 3150
sales@moffat.co.nz



Designed and manufactured by




ISO9001
All Waldorf Bold products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.


In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
AN.WBD.S.01.23


INLB8100W-B




INLB8100W-CD



INLB8100W-LS



INLB8100W3 / INLB8100W5



SPECIFICATIONS

Cooktop

3.5kW induction wok
or
5kW induction wok
Ø 300mm induction

Electrical requirements

INLB8100W3

3.5kW, 220-240V, 50/60Hz, 1P+N+E
16A

INLB8100W5

5.0kW, 380-415V, 50/60Hz, 3P+E
8A / phase

Electrical connection

130mm from LH side, 30mm from rear,
635 from floor

Dimensions

Bench model

Width 450mm
Depth 805mm
Height 415mm
Incl. splashback 630mm
Incl. low back 470mm

All models (excluding Bench model)

Width 450mm
Depth 805mm
Height 915mm
Incl. splashback 1130mm
Incl. low back 970mm

Nett weight

88kg

Packing data

0.54m3, 130kg
Width 495mm
Depth 865mm
Height 1255mm

OPTIONS AT EXTRA COST

Castors
Plinth mounting

an Ali Group Company



The Spirit of Excellence