



## PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

### PRODUCT

**Waldorf 800 Series IN8400R3F-B - 900mm Electric Induction Cooktop - Bench Model**

**Model / SKU: IN8400R3F-B**

#### KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email [sales@kwcommercial.com.au](mailto:sales@kwcommercial.com.au)

Web [www.kwcommercial.com.au](http://www.kwcommercial.com.au)



Scan for the current KW product page

### DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.


Official supplier source: [https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/IN8400FR\\_AN.pdf](https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/IN8400FR_AN.pdf)

Technical data sheet for

# INDUCTION COOKTOP 900mm

- ROUND & FULL AREA INDUCTION ZONE

IN8400R3F-B, IN8400R3F-LS, IN8400R3F-CB, IN8400R5F-B, IN8400R5F-LS, IN8400R5F-CB



IN8400R5F-LS

- Heavy-duty construction
- Induction zones - two 270mm dia. round on LH side and two 270mm square full area on RH side
- Round induction - 3.5kW or 5kW heating per zone
- Full area induction - 5kW heating per zone
- Automatic pan detection switches induction zone off when pan removed
- 3 models of base unit
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular
- Low back models (INL) available

## Induction Zone Options

- F** - Full area induction
- R3** - 3.5kW round induction
- R5** - 5kW round induction

## Series Options

- IN** - Standard splashback models
- INL** - Low back models
- INB** - Bold vitreous enamel colour front finish on standard splashback models
- INLB** - Bold vitreous enamel colour front finish on low back models

## Overall Construction

### COOKTOP

- Welded hob with 2.0mm stainless steel hob top
- Splashback and side panels 1.2mm stainless steel
- Front panels 0.9mm stainless steel
- 6mm thick ceramic glass cooking surface
- Full area induction on LH side and round induction on RH side available to order

### BENCH MOUNT (supplied as – B model)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet
- Adjustable height 80mm – 105mm

### LEG STAND (supplied as – LS model)

- Fully modular for matched suite finish
- Framed top for connection to Cooktop
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with four adjustable feet
- Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- Quick assembly design

### CABINET BASE (supplied as – CB model)

- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with four adjustable feet

## Controls

- Large easy use control knob
- Infinitely variable power controls for each induction zone
- Heating ON indicator lights (green) including pan detection indication
- Error mode indicator light (green)

## Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Fully sealed cooking surface
- Removable full stainless steel air intake filters (induction cooling)
- Front service access

Technical data sheet for

# INDUCTION COOKTOP 900mm

- ROUND & FULL AREA INDUCTION ZONE

IN8400R3F-B, IN8400R3F-LS, IN8400R3F-CB, IN8400R5F-B, IN8400R5F-LS

## Specifications

### COOKTOP

2 x 3.5kW induction zones or  
2 x 5.0kW induction zones  
and  
2 x 5.0kW full area induction zones  
Ø 270mm and 270mm square induction zones

### Electrical requirements

#### IN8400R3F

17kW, 400-415V, 50/60Hz, 3P+E  
24A / phase

#### IN8400R5F

20kW, 400-415V, 50/60Hz, 3P+E  
28A / phase

### DIMENSIONS

#### Bench model

Width 900mm  
Depth 805mm  
Height 355mm  
Incl. splashback 570mm  
Incl. low back 410mm

#### All models (excluding Bench model)

Width 900mm  
Depth 805mm  
Height 915mm  
Incl. splashback 1130mm  
Incl. low back 970mm

### NETT WEIGHT

105kg



### PACKING DATA

1.03m<sup>3</sup>, 157kg  
Width 945mm  
Depth 865mm  
Height 1255mm



### OPTIONS AT EXTRA COST

Castors  
Plinth mounting



#### IN8400-B




#### IN8400-LS



#### IN8400-CB



#### IN8400R3F IN8400R5F



[moffat.com.au](http://moffat.com.au)  
[moffat.co.nz](http://moffat.co.nz)

Australia  
[moffat.com.au](http://moffat.com.au)

### Moffat Pty Limited

Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone +613-9518 3888  
Facsimile +613-9518 3833  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

New South Wales  
Telephone +612-8833 4111  
[nswsales@moffat.com.au](mailto:nswsales@moffat.com.au)

South Australia  
Telephone +613-9518 3888  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

Queensland  
Telephone +617-3630 8600  
[qldsales@moffat.com.au](mailto:qldsales@moffat.com.au)

Western Australia  
Telephone +618-9413 2400  
[wasales@moffat.com.au](mailto:wasales@moffat.com.au)

### New Zealand

[moffat.co.nz](http://moffat.co.nz)

### Moffat Limited

Rolleston  
45 Illinois Drive  
Izone Business Hub  
Rolleston 7675  
Telephone +64 3-983 6600  
Facsimile +64 3-983 6660  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

Auckland  
Telephone +64 9-574 3150  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd  
AN.W8.01/22

an Ali Group Company



The Spirit of Excellence