



GasMax Superfast LPG Gas Tube Fryer - RC300ELPG

Quick Overview

- Oil Capacity 18 Litre
- Tank Capacity 23 Litre
- Dimensions 1195(H) x 395(W) x 759(D)mm
- All Stainless steel Front, door, tank, and trim
- Model Number RC300E
- Temperature Range 120 ° C to 200 ° C
- Nett Weight 49.6kg
- 18-litre oil capacity
- 25kg/hr production rate
- 90MJ multi-jet burner system
- Reliable Millivolt Mechanical controls
- Easy cleaning, installation, and service
- Supplied with 2 baskets
- Stainless steel lid supplied as standard
- 1/2 inch Gas Inlet
- IAPMO approved #GMK10174
- Robshaw valve
- Built-in Flue Deflector
- Flame Failure protection as standard
- Adjustable legs
- All components are easily accessible and replaceable from the front
- Stainless steel basket hanger lifts off for easy cleaning
- Food particles fall below burner tubes into a cold zone, which increases oil life
- 32mm ball-type full port drain valve prevents clogging
- Standby pilot for easy start
- Consumption: 82.5 MJ/h

Description

GasMax Superfast LPG Gas Tube Fryer - RC300ELPG

Make the perfect fried fish, chips, and much more with the powerful and reliable GasMax single-tank fryer. With an impressive output, serving large quantities of crispy fried food is easy and ideal for restaurants, takeaways, and other similar establishments. Once service has finished, cleaning is simple thanks to the robust stainless steel construction and oil drainage valve.

Key Features

- Oil Capacity 18 Litre
- Tank Capacity 23 Litre
- Dimensions 1195(H) x 395(W) x 759(D)mm
- All Stainless steel Front, door, tank, and trim
- Model Number RC300E
- Temperature Range 120 ° C to 200 ° C
- Nett Weight 49.6kg
- 18-litre oil capacity
- 25kg/hr production rate
- 90MJ multi-jet burner system
- Reliable Millivolt Mechanical controls
- Easy cleaning, installation, and service
- Supplied with 2 baskets
- Stainless steel lid supplied as standard
- ½ inch Gas Inlet
- IAPMO approved #GMK10174
- Robshaw valve
- Built-in Flue Deflector
- Flame Failure protection as standard
- Adjustable legs
- All components are easily accessible and replaceable from the front
- Stainless steel basket hanger lifts off for easy cleaning
- Food particles fall below burner tubes into a cold zone, which increases oil life
- 32mm ball-type full port drain valve prevents clogging
- Standby pilot for easy start
- Consumption: 82.5 MJ/h

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Connection Type	LPG
Net Weight (Kg)	65
Width (mm)	394
Depth (mm)	759
Height (mm)	1195
Packing Width (mm)	800
Packing Depth (mm)	600
Packing Height (mm)	1200
Power	82.5 MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice