



Ex-Showroom: Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse - CO-402BDD-VIC1012

Quick Overview

Lot Number: VIC1012

Class: 1

Conditions: Ex-showroom display unit.

Warranty: 2 Years

Description

Ex-Showroom: Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser cold rinse - CO-402BDD-VIC1012

- Lot Number:
- VIC1012
- Class:
- 1
- Conditions:
- Ex-showroom display unit.
- Warranty:
- 2 Years

Key Features

Fagor EVO-CONCEPT glass washer with drain pump and detergent & rinse dispenser, cold rinse CO-402BDD

E-VO CONCEPT glass washer with 350x350 mm basket (CO-352) and 400x400 mm basket (CO-402) with double wall rigid door. Dish service height up to 220 mm (CO-352) and 270 mm (CO-402). Constant water consumption of 2 litres per cycle for the rinse with a mains pressure of 2 bar. New optimised hydraulic EFFI-WASH system, with stainless steel wash arms and 0.26 kW pump, guaranteeing a top quality, effective and efficient wash with an optimum Sinner circle balance. It also has a built-in rinse aid dispenser and drainage pump (B) and detergent dispenser (DD) fitted at factory or supplied in kit form. It has adjustable feet to permit levelling according to the needs of the establishment. Magnetic door open sensor. Electronic control panel making it easy to use.

- Front loading glasswasher - EVO Generation - Advance range.
- Basket size: 400 x 400 mm.
- Hourly production: 40 baskets/hour.

- Clearance (max ware height): 275 mm.
- Valid for dishes Ø 270 mm.
- Wash cycles: 90" - 120" - 180".
- Electronic control. Digital displays.
- Selector for an optional cold rinse at the end of the cycle.
- Made of stainless steel.
- The door has double skin.
- Double rotating wash and rinse systems, above and below, made of stainless steel.
- Wash pump: 260 W.
- Drain pump: 30 W. Drainage cycle.
- Tank with 2.0 kW heating element.
- Tank capacity: 13 litres.
- Boiler with 2.8 kW heating element.
- Boiler capacity: 4 litres.
- Water consumption: 2.4 litres/rinse.
- Thermostatic temperature control: washing at 60 °C and rinsing at 90 °C.
- Security thermostats.
- Built-in automatic rinse dispenser and detergent doser.
- Built-in non-return valve.
- Safety magnetic switch for door opening.
- Adjustable legs.
- WaterMark approved
- Total power: 3.06 kW.
- Dimensions: 470 x 520 x 720 mm.
- Equipment: one basket 400x400, one supplement for dishes and one cutlery container.

Your Shipping Specifications

Product Condition	2ND
Net Weight (Kg)	36
Width (mm)	470
Depth (mm)	520
Height (mm)	720
Packing Width (mm)	530
Packing Depth (mm)	680
Packing Height (mm)	890
Power	11.02 MJ