

CONCEPT

iKORE 202

PureSteam or DirectSteam



General information

FIELD	DATA	Version ⚡ ELECTRIC (E)	🔥 NATURAL GAS (G)
Capacity (standard)	Racks and tray type of trolley (T)*	20 GN2/1 (40 GN1/1)	20 GN2/1 (40 GN1/1)
	Spacing between rack rails	63mm	63mm
Energy supply (standard)	Electric / gas power	67,2 kW	1,55 kW / 65 kW
	Frecuency	50/60 Hz	50 Hz
	Voltage	380-415V 3N	230V 1N
Dimensions and weight	Width	1.165 mm	1.165 mm
	Depth (with handle)	1.074 mm (1.140 mm)	1.074 mm (1.140 mm)
	Height (with hinge)	1.840 mm (1.871 mm)	1.840 mm (1.871 mm)
	Net weight (gross)	~338Kg (403,5Kg)	~357Kg (422,5Kg)

Codes and prices

HUMIDITY	WASHING	SHOWER	MODEL	⚡ CODE	€	🔥 CODE	€
PureSteam boiler	Solid iWash	●	CPW-202-(E/G) R SW S T	19075005	-	19088276	-
		-	CPW-202-(E/G) R SW T	19107465	-	19107466	-
	Spray mode	●	CP-202-(E/G) R S T	19096903	-	19096905	-
		-	CP-202-(E/G) R T	19098472	-	19107464	-
DirectSteam injection	Solid iWash	●	CW-202-(E/G) R SW S T	19107469	-	19107480	-
		-	CW-202-(E/G) R SW T	19078517	-	19091669	-
	Spray mode	●	C-202-(E/G) R S T	19107467	-	19107468	-
		-	C-202-(E/G) R T	19078544	-	19088274	-

Configurable options

OPTION	NAMING	DESCRIPTION	CONF. CODE	€
Washing	LW*	Liquid iWash *Only available for models with W	0104-0002	-
REG4	REG4	Water regulations and compliance - British Standard Approved	0112-0001	-

* Consult for other trolley configurations (T)

VOLTAGE OPTIONS	CONF. CODE	€	GAS OPTIONS	CONF. CODE	€
⚡ 230V 3~ 50/60Hz	0102-0051	-	Butane-Propane LPG	0101-0001	-
⚡ Marine 440V 3~ 50/60Hz	0102-0053	-	Town gas TG	0101-0002	-
⚡ 230V 1N 60Hz	0102-0057	-			
🔥 230V 2~ 50Hz	0102-0058	-			
🔥 230V 2~ 60Hz	0102-0059	-			