

Press Liner Upright Fridge & Freezer with Wi-Fi Controller



Premium Performance, Smart Control And Outstanding Energy Efficiency.

The FED-X Press Liner Upright Fridge & Freezer range is designed for commercial kitchens, cafés, restaurants and foodservice operators who demand reliability, hygiene and efficiency. With 100mm high-density insulation and GEMS energy efficiency ratings up to 9–10 stars, this range delivers exceptional performance while reducing running costs.



XUPC700
Single Door Fridge
XUPF700
Single Door Freezer

XUPC1400
Double Door Fridge
XUPF1400
Double Door Freezer

- Single-door and double-door models available
- Wi-Fi controller supports remote monitoring and alerts
- Climate Class 5 rated for 43°C ambient temperatures
- Stainless steel interior and exterior for easy cleaning
- 103mm high-density insulation for better thermal retention
- Fan-Forced Cooling for even temperature distribution
- R290 natural refrigerant, compliant with Australian standards
- Digital temperature display with core probe included
- Self-evaporative drain reduces manual emptying
- LED internal lighting for clear product display
- Recessed handles, castors and levelling feet for practical use
- Rodent protection and lock provision for secure storage
- Press Liner sealing helps minimise cold air leakage
- GN 1/1 compatible, with each shelf holding two 1/1 GN pans. Single-door models include 15 shelves, and double-door models include 15 x 2 shelves, 530W x 650D mm
- Press Liner runners support shelving on both sides, with a central holder on double-door models.



WI-FI ENABLED

Remote temperature monitoring and control from anywhere.



ENERGY EFFICIENT

GEMS energy efficiency ratings up to 9–10 stars to help lower running costs.



PREMIUM INSULATION

100mm high-density insulation for superior thermal retention.



BUILT TO LAST

Stainless steel interior and exterior for hygiene, durability and easy cleaning.



NATURAL REFRIGERANT

R290 natural refrigerant, compliant with Australian standards.

Wi-Fi ENABLED








Remote Monitoring



Temperature Alerts



Remote Control



Code	Gross Capacity (L)	Net Capacity (L)	Dimensions (WxDxH mm)	Net Weight (kg)	Temp. Range (°C)	Ambient (°C)/RH%	Voltage (V)	Power (W/A)
Single Door Fridge								
XUPC700	511	454	740x870x2010	113	+2 to +8	43/60	240	177/10
Single Door Freezer								
XUPF700	511	454	740x870x2010	119	-22 to -18	43/60	240	265/10
Double Door Fridge								
XUPC1400	1194	1057	1480x870x2010	182	+2 to +8	43/60	240	229/10
Double Door Freezer								
XUPF1400	1194	1057	1480x870x2010	183	-22 to -18	43/60	240	510/10

Allow 100mm clearance for installation, all vents must be left clear.

Prices and specifications are subject to change without notice. Pictures are for illustrative purpose and final product may differ