



FED-X Three Door Salad Prep Fridge with Glass Top - XS903GC

Quick Overview

- Gross Volume: 368L
- Net Volume: 218L
- Max Ambient Temperature: 38°C, 60%RH
- Cooling System: Fan-assisted
- Temperature Range: +2 to +8 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Glass canopy with ambient middle shelf
- Open top suitable for multiple pan configurations (Pans and lids are not included)
- Replaceable magnetic door seals. User-friendly Digital controls
- Integrated cutting board made from high-density polyethylene
- Pan and pan cover must be used to ensure the correct operating temperature
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1295mm W x 595mm D x 455mm H

Â

Description

FED-X Three Door Salad Prep Fridge with Glass Top - XS903GC

Key Features

- Gross Volume: 368L
- Max Ambient Temperature: 38°C, 60%RH
- Cooling System: Fan-assisted
- Temperature Range: +2 to +8 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Glass canopy with an ambient middle shelf
- Open top suitable for multiple pan configurations (Pans and lids are not included)
- Replaceable magnetic door seals. User-friendly Digital controls
- Integrated cutting board made from high-density polyethylene
- Pan and pan cover must be used to ensure the correct operating temperature

- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1295mm W x 595mm D x 455mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	3
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	368L
Net Volume	218L
Max Ambient Temperature	38°C, 60%RH
Temperature Range	+2 to +8 ° C
Net Weight (Kg)	104
Width (mm)	1365
Depth (mm)	700
Height (mm)	1310
Packing Width (mm)	1390
Packing Depth (mm)	730
Packing Height (mm)	1050
Power	240V, 240W/1.6A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice