



Gasmax 4 Burner With Oven Flame Failure GBS4TS

Quick Overview

- Stainless steel front, galvanized sides
- Natural Gas
- Cast iron open burner
- Thermostat (100° C- 300° C) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Stainless steel oven door with good insulation
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400° C; heat

Description

Gasmax 4 Burner With Oven Flame Failure GBS4TS

Key Features

- Stainless steel front, galvanized sides
- Natural Gas
- Cast iron open burner
- Thermostat (100° C- 300° C) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Stainless steel oven door with good insulation
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing

- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400°C heat

2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Net Weight (Kg)	132
Width (mm)	610
Depth (mm)	855
Height (mm)	1128
Packing Width (mm)	730
Packing Depth (mm)	1030
Packing Height (mm)	890
Power	182MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice