



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Hoshizaki RTC-90DEA-GN-3D Underbench Drawer Refrigerator – 160L

Model / SKU: RTC-90DEA-GN-3D

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au









Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: /media/products/71761/documents/hoshizaki-rtc-90dea-gn-3d-spec-sheet-a313912c6475__kw.pdf



ITEM	Hoshizaki Drawer Type Undercounter Refrigerator
MODEL	RTC-90DEA-GN-3D
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity: 0.42kVA(1.91A)
AMPERAGE	Rated: 1.5A
ELECTRIC CONSUMPTION	Motor: *W(Power Factor: *) Heater: 188W Refrigeration: *W Defrost: 188W
HEAT REJECTION	*W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	160L
OUTSIDE DIMENSIONS	900mm(W) x 700mm(D) x 815mm(H)
INSIDE DIMENSIONS	530mm(W) x 533mm(D) x 588mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic 110W
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a/160g
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -6 to 12°C
DEFROST CONTROL	Microprocessor Controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector
LEG	Urethane (76mm DIA, 115mm HIGH)
WEIGHT	80kg (Gross Approx. *kg)
PACKAGE	Carton 965mm(W) x 780mm(D) x 950mm(H)
OPERATING CONDITIONS	Ambient Temperature: 5-43° C Voltage Range: Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.
Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pull-down temperature at ambient temperature of 32° C and power supply of 230V 50Hz.
The amperage and electric consumption are based on measurements at ambient temperature of 32° C and power supply of 230V 50Hz.
3. The cabinet temperature range of -6 to 12° C is guaranteed at ambient temperature of 30° C.
4. Product code: T012-C814

HOSHIZAKI DRAWER TYPE UNDERCOUNTER REFRIGERATOR RTC-90DEA-GN-3D

APPROVED KAWAKAMI	CHECKED WANG	DESIGNED LIU	DRAWN ZHANG	SCALE 1/20	TRIGONOMETRY
* * *	* * *	*****	DATE 2019.02.15	DRAWING NO. D24507	SYMBOL △
APPROVED	DESIGNED	SYMBOL	DATE		