



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Washtech AL - Professional High Capacity Passthrough Dishwasher - 600mm Rack

Model / SKU: AL

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/AL_au.pdf

AL

HIGH CAPACITY PASSTHROUGH DISHWASHER

WASHTECH®



STANDARD FEATURES

- 40, 60 and 90 second cycles
- Wash capacity of up to 1980 plates per hour
- Compatible with 600x500 racks - 5 GN pans or 22 plates
- Touchscreen controls with versatile Heads Up Display
- Powerful 1.5HP soft start wash pump
- Dual chemical pumps
- Insulated front hood
- Assured rinse with dual boilers and booster pump
- Hands-free drainage system with sump and drain pump
- Two-stage stainless steel wash and drain filtration
- Heavy-duty stainless-steel construction and manifold
- Independent stainless-steel wash and rinse arms

- 1x 600mm GN tray rack (600 70042)
- 1x 500mm dish rack (600 70028)
- 1x 500mm cup rack (600 70029)
- 1x cutlery container (C660503)
- 1x plumbing connection kit (water and chemical hoses)

SPECIFICATIONS

A - Hot Water

Temperature	65°C*
Connection	3/4" male, hose supplied
Pressure	100-500kPa
Flow	10L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.4L per cycle


D - Drainage

Drain pump flexi-hose	25mm
-----------------------	------

C - Electrical	V	Hz	A/ph	Max kW
Three phase	400	50	15	9.00

*Suitable for connection to low inlet temp, flow and/or pressure supplies. Isolating switch must be within 1m of, and not directly behind, the machine. Refer to operator manual for installation instructions.

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.



	Machine	Packed
Dimensions		
Width (mm)	775	760
Depth (mm)	710	820
Height (mm)	1530	1460
Weight (kg)	125	146
Volume (m3)		0.91
Water Quality	Min	Max
pH	7	8
TDS	1	135
Cl-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

Corner Installation Notes:

- a. Machine should be installed so racks are pushed into the back of the machine.
- b. Allow 300mm clearance to front for service access.
- c. Splashback return to be no higher than 150mm.

Touchscreen Control:

- a. Bracket supplied with controls enables install either side, under bench or on wall.
- b. Consult Operator Manual for full details on correct installation.



moffat.com.au | 1300 269 801

Manufactured in New Zealand by Washtech Limited - Distributed in Australia by Moffat PTY Limited
© Copyright Washtech Limited / Washtech ALC Series-5 / WALC0040 / Feb-25

an Ali Group Company



the spirit of excellence