



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Washtech GL-B - Compact Undercounter Polish-Free Compatible Glasswasher - 450mm F

Model / SKU: GL-B

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://moffat.global.ssl.fastly.net/sites/default/files/products/specification/Washtech_GL_AU.pdf

GL

COMPACT UNDERCOUNTER POLISH-FREE COMPATIBLE GLASSWASHER

WASHTECH®



STANDARD FEATURES

- 1, 2 and 3 minute cycles
- Full insulation and soft close door
- Polish-free glasswashing compatible (add BA14-DW14)
- Capacity of up to 960 glasses per hour
- Tilting rack slide compatible with 365mm to 450mm racks
- Touchscreen controls providing advanced customisation
- 0.3HP soft start wash pump
- Dual chemical pumps
- Assured rinse c/w break tank and booster pump
- Hands-free drainage system with sump and drain pump
- Stainless steel wash and drain filter basket
- Independent stainless steel wash and rinse arms
- Updatable power for rapid rinse recovery (8kW on 3p/15A)
- Heavy-duty stainless steel construction
- Also available in mirror or matte black stainless steel (GL-B)
- 1x 450mm dish rack (600 70081)
- 1x 450mm cup rack (600 70080)
- 1x cutlery container (C660503)
- 1x upgrade connection kit (all hoses and 1p/15A plugset)

SPECIFICATIONS

A - Water^

Temperature	20-65°C*
Connection	3/4" male, hose supplied
Pressure	100-500kPa
Flow	10L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.4L per cycle


D - Drainage

Drain pump flexi-hose	25mm
-----------------------	------

C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.25
Single phase	230-240	50	25	5.25
Three phase	400-415	50	15	9.00

*Upgrade kit available to enable switchable inlet water and on-demand selection of polish-free mode using cold RO water (requires a BA14-DW14), and high capacity mode using a standard hot water feed.

Isolating switch must be within 1m of, and not directly behind, the machine
Refer to operator manual for installation instructions



Dimensions

	Machine	Packed
Width (mm)	527	560
Depth (mm)	600	650
Height (mm)	840	875
Weight (kg)	68	71
Volume (m3)		0.32

Water Quality

	Min	Max
pH	7	8
TDS	1	135
Cl-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

*Suitable for connection to cold water supply. To minimise recovery time between cycles it is recommended that a 1p/25A or 3/15A power supply is used in conjunction with cold inlet water.

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.



moffat.com.au | 1300 269 801

Manufactured in New Zealand by Washtech Limited - Distributed in Australia by Moffat PTY Limited
© Copyright Washtech Limited / Washtech GL Series-8 / WGL0040 / Jun-25



an Ali Group Company



the spirit of excellence