



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Hoshizaki 97000191 HF-77-GN 628L Gastronorm Freezer 1 Door

Model / SKU: 97000191

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au




Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: </media/products/82220/documents/other-3.pdf>

NOTE: COMPONENT AND ASSEMBLY MUST BE COMPLIANT TO APPLICABLE RECENT ROHS DIRECTIVES.




*WE RESERVE THE RIGHT TO MAKE CHANGES IN SPECIFICATIONS AND DESIGN WITHOUT PRIOR NOTICE

1. INSTALL THE PRODUCT PROPERLY IN ACCORDANCE WITH THE INSTRUCTIONS ON LOCATION, ELECTRICAL CONNECTIONS STATED IN THE INSTRUCTION MANUAL PROVIDED.
ALLOW 10MM EXTRA SPACE AT THE INSTALLATION SITE TO MEET ANY INSTALLATION REQUIREMENTS (ADDITIONAL SPACING IS ALSO REQUIRED FOR PROPER AIR FLOW AND PIPE CONNECTIONS).
2. THE HEAT REJECTION IS BASED ON THE REACHED PULL DOWN TEMPERATURE AT AMBIENT TEMPERATURE OF 43°C AND POWER SUPPLY OF 230VAC 50HZ.
THE AMPERAGE AND ELECTRIC CONSUMPTION ARE BASED ON MEASUREMENT AT AMBIENT TEMPERATURE OF 43°C AND POWER SUPPLY OF 230VAC 50HZ.

THIS ASSEMBLY DRAWING IS FOR ILLUSTRATION PURPOSE.
COMPONENTS, ASSEMBLY SEQUENCE MAY VARY DEPENDING UPON MANUFACTURING PRACTICES SPECIFIC TO MANUFACTURING LOCATIONS.
REFER PROCESS WORK INSTRUCTIONS FOR MORE DETAILS ON ASSEMBLY.
REFER SAP BOM FOR EXACT MATERIAL CONSUMPTION.

COATED / SS SHELF
(D: 610 X W: 540)
GN PAN 2/1 X 1NOS
OR GN PAN 1/1 X 2NOS



REVISION SHEET NO		ZONE	CHANGE NOTE		ECN	DATE	DRAWN

- OPTIONS:
1. BOTTOM & REAR PANEL CAN BE AVAILABLE IN SUS 430/ SUS304
 2. ALL EXTERIOR & INTERIOR CAN BE AVAILABLE IN SUS 304
(IN THIS OPTION BOTTOM & REAR PANEL ARE PAINTED)

ITEM	HOSHIZAKI FREEZER
MODEL	HFWE77LS4-LDGN
POWER SUPPLY	SINGLE PHASE, 230V AC, 50HZ
RATED CURRENT	1.8 AMPS
RATED POWER	400 W
HEAT REJECTION	887 W
POWER CORD	10 AMPS / 3 METER
EFFECTIVE CAPACITY	383 LITRE
OUTSIDE DIMENSIONS	700 (W) X 881 (D) X 2024 (H - WITH CASTOR)
INSIDE DIMENSIONS	596 (W) X 700 (D) X 1505 (H)
EXTERIOR	SS 430 HAIRLINE NO 4 FINISH, GALVANIZED STEEL POWDER COATED (REAR/BOTTOM)
INTERIOR	SS 430 HAIRLINE NO 4 FINISH
INSULATION	POLYURETHANE FOAM (CFC FREE)
INSULATION FOAM BLOWING AGENT	CYCLOPENTANE
REFRIGERATION SYSTEM	FORCED AIR CIRCULATION
DEFROST STSTEM	IN COMPRESSOR OFF CYCLE
COMPRESSOR	HERMETIC 766 W
CONDENSER	FORCED (WIRE ON TUBE)
EVAPORATOR	FORCED (FIN & TUBE)
REFRIGERANT/ CHARGE	R-290 / 80 gram
TEMP. CONTROL	ELECTRONIC ADJUSTABLE FROM -18°C TO -22°C
DEFROST CONTROL	BY TEMPERATURE CONTROLLER
ELECTRIC CIRCUIT PROTECTION	NON RESETTABLE FUSE (GLASS FUSE), 10 AMP
COMPRESSOR PROTECTION	MOTOR PROTECTOR
CASTOR	NON ADJUSTABLE 4 NOS
GN RAIL / SHELF	4 SET GN RAIL, 4 PLASTIC COATED STANDARD SHELVES (SS SHELVES OPTIONAL)
WEIGHT	NET: 125KG (GROSS: APPROX 148KG)
PACKAGE	CARTON (WOODEN PALLET) 785MM (W) X 994MM (D) X 2090MM(H)
ASSESSORIES	GN RAILS & SHELVES
OPERATING CONDITIONS	AMBIENT TEMPERATURE : 10 TO 43°C VOLTAGE RANGE RATED VOLTAGE ±6%
CABINET LAMP (FOR LS4 VERSION)	C-TYPE 510MM, 2W, DC24V
LAMP DRIVER (FOR LS4 VERSION)	ELECTRONIC DRIVER 20W

UNSPECIFIED TOLERANCES							SCALE: NTS  ALL DIMENSIONS ARE IN MM		TITLE REACH-IN REFRIGERATOR			DWG. NO: 0712748		REVISION A			
DIM	<6	6-30	30-120	120-400	400-1000	>1000	DRAWN BY PUSHPENDRA			MODEL HFWE77LS4-LDGN			SAP CODE --				
TOL	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2											
UNSPECIFIED TOL. ON ANGLE ±0.5							CHECKED BY KIRAN			RELEASE DATE 20.11.2024		SHEET 1 OF 1					
1 * DIMENSIONS ARE IMPORTANT. 2 REFERENCE DIMENSIONS ARE MARKED WITH "R" 3 PART SHOULD BE FREE FROM SHARP EDGES & BURRS							APPROVED BY PRATAP			RELEASE STAGE: RELEASED							
REFERENCE STANDARD -																	

1. DIMENSIONS ARE IMPORTANT.
2. REFERENCE DIMENSIONS ARE MARKED WITH "R".
3. PART SHOULD BE FREE FROM SHARP EDGES & BURRS

REFERENCE STANDARD

-