



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Hoshizaki 91000169 IM-240PE-28 180KG CUBE ICE MAKER – SELF CONTAINED

Model / SKU: 91000169

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: /media/products/82244/documents/spec_sheet-3.pdf



HOSHIZAKI

IM - 240PE - 28 - F


Model Number
91000170

Cube 180kg Ice Maker with Drain Pump - Self Contained



Hoshizaki IM-240PE-F FlexiCube model is a self-contained ice maker with internal drain pump producing up to 195kg (10°C Air temp; 10°C Water) of cube ice per 24 hours.

- Produces compact, dry, tasteless and slow melting cube ice, allowing just the right amount of dilution.
- Automated cleaning (wash auto-restart).
- Water circuit cleaning notification.
- Condenser cleaning notification.
- Magnetic dc pump motor with variable speed.
- High grade stainless steel.
- Stand-by/wash buttons.
- Removable door gasket.
- Easy-clean air filter.
- Flexicube models include an integrated drain pump, enabling flexible placement of the ice maker, regardless of drain position or height.
- Internal drain pump models allow for positioning radius of 10m distance and up to 1.5m height to drain point (based at max 10m distance).



Cube Size: **STANDARD**
Weight: 23 g

PRODUCT SPECIFICATION

Ice Type	Cube
Production Capacity per 24hours	pprox. 195kg @ 10°C Air temp; 10°C Water Approx. 180kg @ 21°C Air temp; 15°C Water Approx. 160kg @ 32°C Air temp; 21°C Water
Max Storage Capacity	Approx. 110kg (Bin Control Setting Approx. 80kg)
Dimensions	704mm (W), 665mm (D), 1580mm (H)
Weight Net Packed Weight	109kg 122kg
Cooling	Air
AC Supply Voltage	1 PHASE 220-240V 50Hz/ 10 AMP Plug
Refrigerant	R290
Operating Conditions	Ambient Temp.: 1-40°C Water Supply Temp.: 5-35°C Water Supply Pressure: 0.07-0.8MPa (0.7 - 8bar) Voltage Range: Rated Voltage ±6%
Water Consumption Per 24h	Approx. 0.67m ³ @ 10°C Air temp; 10°C Water Approx. 0.32m ³ @ 21°C Air temp; 15°C Water Approx. 0.29m ³ @ 32°C Air temp; 21°C Water
Heat Rejection (AT 32°C, WT 21°C)	2580W
Accessories included	Installation kit, Scoop
GEM Number	AIM0022

INSTALLATION REQUIREMENTS

- Ensure the condenser is cleaned periodically as per the manufacturer's manual.
- Do not plug the unit into multi-plug power boards with other appliances
- Room ventilation or air conditioning can improve the situation by reducing the humidity.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

*Refer to manual for full installation & maintenance requirements.



For free 6 month extended warranty, register online within 4 weeks of purchase date.
hoshizaki.com.au

Descriptions and specifications are subject to change at any time, without notice.
Illustrations for demonstration purposes. Copyright © 2026 Hoshizaki Lancer Pty Ltd. All rights reserved.




HOSHIZAKI

IM - 240PE - 28 - F

Cube 180kg Ice Maker with Drain Pump - Self Contained

TECHNICAL DRAWING



For free 6 month extended warranty, register online within 4 weeks of purchase date.

hoshizaki.com.au

Descriptions and specifications are subject to change at any time, without notice.
Illustrations for demonstration purposes. Copyright © 2026 Hoshizaki Lancer Pty Ltd. All right reserved.