



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Hoshizaki 96000008 4DM Ice Bin Top Kit

Model / SKU: 96000008

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: /media/products/82264/documents/spec_sheet-5.pdf

- | | | | |
|-------------------------------|---|------------------|--|
| ITEM | Hoshizaki Cube Ice Maker | | |
| MODEL | IM-240XPE | | |
| POWER SUPPLY | 1 Phase 220-240V 50Hz
Capacity: Min. 1.77kVA (7.4A) | | |
| AMPERAGE | Running: 3.7A Rated Motor: 3.7A
Starting: 27A | | |
| ELECTRIC CONSUMPTION | Rated Motor: 845W (Power factor: 94%)
(20.3kWh/24h, 14.2kWh/100kg) | | |
| ICE PRODUCTION PER 24h | Approx. 195kg(5mm)/210kg(15mm)(AT.10°C WT.10°C)
Approx. 180kg(5mm)/195kg(15mm)(AT.21°C WT.15°C)
Approx. 160kg(5mm)/175kg(15mm)(AT.32°C WT.21°C) | | |
| WATER CONSUMPTION PER 24h | Approx. 0.67m ³ /d (AT.10°C WT.10°C)
Approx. 0.32m ³ /d (AT.21°C WT.15°C)
Approx. 0.29m ³ /d (AT.32°C WT.21°C) | | |
| SHAPE OF ICE | Cube Approx 28 x 28 x 32mm | | |
| FREEZE CYCLE TIME | Approx. 21min (AT.21°C WT.15°C) | | |
| ICE PRODUCTION PER CYCLE | Approx. 3.5kg/140pcs (AT.21°C WT.15°C) | | |
| OUTSIDE DIMENSIONS | 1084mm(W) x 700mm(D) x 500mm(H) | | |
| EXTERIOR | Stainless Steel | | |
| INSULATION | Polyurethane Foam | | |
| INSULATION FOAM BLOWING AGENT | Water Blown | | |
| CONNECTIONS - ELECTRIC | X-Type Con. (with CONT. Plug) | | |
| CONNECTIONS - WATER SUPPLY | Inlet G3/4 (connected at rear side) | | |
| CONNECTIONS-DRAIN | Outlet R3/4 (connected at rear side) | | |
| ICE MAKING SYSTEM | Cell type | | |
| HARVESTING SYSTEM | Hot Gas Defrost | | |
| COMPRESSOR | Hermetic | | |
| CONDENSER | Fin and Tube type Air-cooled | | |
| HEAT REJECTION | 2250W (1940kcal/h)(AT.32°C WT.21°C) | | |
| EVAPORATOR | Tin-plated Copper Tube on Sheet and Cells | | |
| REFRIGERANT CONTROL | Thermostatic Expansion Valve | | |
| REFRIGERANT CHARGE | R290/147g | | |
| ICE MAKING CONTROL | Thermistor Timer | Controller Board | |
| HARVESTING CONTROL | Thermistor | | |
| BIN CONTROL | Microswitch (with Time Delay) | | |
| ICE MAKING WATER CONTROL | Timer Water Pan's Movement | | |
| ELECTRICAL PROTECTION | Class I Appliance 5A Fuse | | |
| COMPRESSOR PROTECTION | Auto-reset Overload Protector | | |
| ICE MAKING PROTECTION | Interlock by Controller Board | | |
| NET WEIGHT | 78kg (Gross 93kg) | | |
| PACKAGE | Carton 1196mm(W) x 825mm(D) x 640mm(H) | | |
| ACCESSORIES | Scoop Installation Kit Brace | | |
| OPERATING CONDITIONS | Ambient Temp.: 1 - 40°C Water Supply Temp.: 5-35°C
Water Supply Pressure: 0.07-0.8MPa (0.7-8bar)
Voltage Range: Rated Voltage±6% | | |

Distributed by KW Commercial Kitchen | 1300 001 366
www.kwcommercial.com.au | sales@kwcommercial.com.au