



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

True TBR36-PTSZ1-L-S-G-G-2 "Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 1 Glass S

Model / SKU: TBR36-PTSZ1-L-S-G-G-2

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://true-middleware.s3.eu-west-1.amazonaws.com/pdfs/aus/TBR36-PTSZ1-L-S-G-G-2.pdf>

TBR36-PTSZ1-L-S-G-G-2


"Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 1 Glass Swing Door Front, 1 Glass Swing Door Rear



Dimensions	
External Width (mm)	914
External Depth (mm)	631
External Height (mm)	881
Exclusions	Depth does not include 35 mm for front + 35 mm for back door handles. Height does not include 7 mm for leg levelers.
Gross Volume (Litres)	350
Supplied Shelves	3
Shelf Size (L x D mm)	394 x 458
Internal Net Height (mm)	730
Unpackaged Weight (kg)	121
Packaged Weight (kg)	132
Packaged Dimensions (W x D x H mm)	1083 x 801 x 1067
Supplied with	Levelling Screws. Optional castors sold seperately.

Build	
Door Description	1 Full Glass Swing Door
Door Opening	Left (standard) or Right Field Reversible
Exterior Construction	Stainless Steel front and countertop. Matching Aluminium sides & rear.
Interior Construction	Stainless Steel
Air Intake Position	Front
Ventilation Position	Front
Clearance Required	Zero back and sides
Cord Length (Meters)	3.04
Internal Lighting	TruLumina®
Standard w/ Locks	Standard

Technical	
Temperature Range	0.5 : 3.3°C
Refrigerant	R290
Voltage/Frequency/Phase	220-240V/50-60Hz/1
Amps	1.8
Watts	414
Defrost Type	Auto



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

[0800 783 2049](tel:08007832049)
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



36" [914]

27/32" [56]

1 3/4" [44]

34 11/16" [881]

31 11/16" [805]

25/32" [20]

11 19/32" [294]

23 5/8" [600]

GLASS DOOR
VIEWING AREA
17 5/8" [448] X
25 11/16" [652]

DOOR OPENING
20 9/32" [515] X
28 5/16" [719]

POWER
CORD
EXIT

30" [762]

26 15/16" [684]

22 3/4" [578]

30 27/32" [783]

Ø 1" [25]
ACCESS
OPPOSITE
CONDENSING
UNIT

22 3/4" [578]

3 15/16" [100]

4 5/16" [110]

26 9/16" [675]

16 3/4" [425]

Ø 2 1/4" [57]
FLOOR
ACCESS

7 3/4" [197]

Ø 1" [25]
DRAIN
ACCESS

7 1/32" [179]

6 13/32" [163]

18 3/4" [476]

72 13/32" [1839]

22 23/32" [577]

20 13/32" [518]

R22 31/32" [583]



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

