



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

True TBR60-PTSZ1-L-S-SS-SS-2 "Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 2 Solid

Model / SKU: TBR60-PTSZ1-L-S-SS-SS-2

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: <https://true-middleware.s3.eu-west-1.amazonaws.com/pdfs/aus/TBR60-PTSZ1-L-S-SS-SS-2.pdf>

Bar Refrigeration

TBR60-PTSZ1-L-S-SS-SS-2

"Pass-Thru" Bar Refrigerator, Stainless Steel Ext, 2 Solid Swing Doors Front, 2 Solid Swing Doors Rear



Dimensions	
External Width (mm)	1524
External Depth (mm)	631
External Height (mm)	881
Exclusions	Depth does not include 35 mm for front + 35 mm for back door handles. Height does not include 7 mm for leg levelers.
Gross Volume (Litres)	550
Supplied Shelves	6
Shelf Size (L x D mm)	551 x 458
Internal Net Height (mm)	730
Unpackaged Weight (kg)	182
Packaged Weight (kg)	193
Packaged Dimensions (W x D x H mm)	1690 x 801 x 1067
Supplied with	Levelling Screws. Optional castors sold seperately.

Build	
Door Description	2 Solid Swing Doors
Exterior Construction	Stainless Steel front and countertop. Matching Aluminium sides & rear.
Interior Construction	Stainless Steel
Air Intake Position	Front
Ventilation Position	Front
Clearance Required	Zero back and sides
Cord Length (Meters)	3.04
Internal Lighting	LED
Standard w/ Locks	Standard

Technical	
Temperature Range	0.5 : 3.3°C
Refrigerant	R290
Voltage/Frequency/Phase	220-240V/50-60Hz/1
Amps	1.3
Watts	299
Defrost Type	Auto



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



Technical drawings of the R22 31/32 inch condensing unit, showing dimensions in inches and millimeters.

Front View (Top):

- Overall Width: 60" [1524]
- Overall Height: 34 11/16" [881]
- Top Flange Height: 1 3/4" [44]
- Door Opening: 20 9/32" [515] X 28 5/16" [719]
- Door Opening Height: 25/32" [20]
- Door Opening Width: 23 5/8" [600]
- Bottom Flange Height: 11 19/32" [294]

Side View (Right):

- Overall Height: 31 11/16" [805]
- Top Flange Height: 2 7/32" [56]
- Power Cord Exit

Top View (Bottom):

- Overall Width: 30" [762]
- Overall Depth: 26 15/16" [684]
- Top Flange Height: 22 3/4" [578]
- Door Opening: 30 27/32" [784]
- Door Opening Height: 3 15/16" [100]
- Door Opening Width: 4 5/16" [110]
- Door Opening Depth: 26 9/16" [675]
- Access Opposite Condensing Unit: ϕ 1" [25]
- Access Floor: ϕ 2 1/4" [57]
- Access Drain: ϕ 1" [25]
- Access Drain Height: 6 13/32" [163]
- Access Drain Width: 18 3/4" [476]
- Access Drain Depth: 72 13/32" [1839]
- Access Drain Height: 22 23/32" [577]
- Access Drain Width: 44 13/32" [1128]
- Access Drain Depth: 7 3/4" [197]
- Access Drain Height: 16 3/4" [425]
- Access Drain Width: 7 1/32" [179]
- Access Drain Depth: 22 31/32" [583]



TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

