



PRODUCT DOCUMENT PACK

Prepared and distributed by KW Commercial Kitchen

PRODUCT

Rieber BKW-KF1 2 x 11 x 2/1 GN Banquet Trolley - Cooled

Model / SKU: BKW-KF1

KW COMMERCIAL KITCHEN

7/72 Canterbury Road, Bankstown NSW 2200

Phone 1300 001 366

Email sales@kwcommercial.com.au

Web www.kwcommercial.com.au



Scan for the current KW product page

DOCUMENT NOTICE

The supplier document begins on the next page. KW contact branding is added in a separate footer area and does not replace the supplier's instructions, specifications or warranty terms.

Official supplier source: https://moffat.global.ssl.fastly.net/sites/default/files/products/range_catalogue/RIEBER_BANQUET_TROLLEY_AU.pdf

***Complete program
Banquet trolley***



[Cold and warm banquet system]



Rieber
[the right solution]



For a successful banquet: Heated or refrigerated food ready for serving

The demands could not be more different: Small or large congresses, seminars, family celebrations in large or small kitchens. No two banquets are ever the same, especially when the quality and the temperature of the food both need to be exactly right. With the Banquet Trolley from Rieber, these requirements can be met economically and appetisingly for the guest. The food can be portioned in advance and parked in pre-heated or refrigerated banquet trolleys until it is time to eat. Even changed schedules or delayed guests are no longer a threat to the success of the banquet.



. . . with the Rieber banquet trolley.

Carcass in stainless steel. Cupboard compartment with seamless deep-drawn shelf rails. Tilt protection (for 115 mm rail clearance) for stainless steel grilles or GN containers. Carcass and doors double-walled and insulated. The compartment divisions comply with Gastronorm dimensions. Doors with silicone seals, automatic click-in catch, can be opened up to 270°/180°. The interior surfaces are smooth and easy to clean. All-round roof gallery and impact frame for heated banquet trolley. Two pushing handles on face side.





Function

Heating without humidity

Check whether the water tray in the base is empty. Close doors, set temperature using the digital control system and press green rocker switch. The control lamp will light up and the circulating air ventilator will start. The digital display shows the temperature development.

Heating with humidity

Before heating, fill the base container up to the rim with water. Replace lid again. You can select the desired humidity level via an extra knob. Heat and humidity are evenly distributed via the special air guides.

Base tray

with air channel for 1-part version

Base tray

with air channel for 2-part version

Central control system

Comprising an ON/OFF switch, digital display, humidity control



The banquet trolley for warm food

The integrated circulating air heating means that +80 °C can be reached in only 30 minutes. The temperature can be regulated from +30 °C to +100 °C by means of a thermostat. Optional, heating with or without humidity.

Units are ready for connection with a 2 m spiral cable, earthed plug and cable holder. Rustproof castors in accordance with DIN 18867 Part 8, wheel diameter 200 mm, 2 fixed castors and 2 swivel castors with brake.

Rated voltage 1 N AC 230 V 50 Hz.



BKW 1 x 2/1 GN heated


Dimensions	777 x 837 x 1712 mm
Empty weight	120 kg
Total connected load	2000 Watt
Clearance between rails	115 mm
Max. no. of stainless steel grilles GN 2/1	11
Storage capacity	
Stacked plates with bowl covers (see top photo on page 4)	
ø 260 mm	64
Plates not stacked	
ø 260 mm	44 (4 per grille)
ø 310 mm	22 (2 per grille)
Order no.	88230104

Clearance between rails	70 mm (without tilt-protection)
Max. no. of stainless steel grilles GN 2/1	18
Storage capacity	
Stacked plates	
ø 260 mm	72 (max. height 60 mm, 4 per grille)
ø 310 mm	36 (max. height 60 mm, 2 per grille)
Order no.	88230105

BKW 2 x 2/1 GN heated

Dimensions	1490 x 837 x 1712 mm
Empty weight	200 kg
Total connected load	2700 Watt
Clearance between rails	115 mm
Max. no. of stainless steel grilles GN 2/1	2 x 11
Storage capacity	
Stacked plates with bowl covers (see top photo on page 4)	
ø 260 mm	160
Plates not stacked	
ø 260 mm	110 (5 per grille)
ø 310 mm	88 (4 per grille)
Order no.	88230203

Clearance between rails	70 mm (without tilt-protection)
Max. no. of stainless steel grilles GN 2/1	2 x 18
Storage capacity	
Stacked plates	
ø 260 mm	180 (max. height 60 mm, 4 per grille)
ø 310 mm	144 (max. height 60 mm, 2 per grille)
Order no.	88230204



Rail clearance:

Describes the maximum useful height between the shelves



*Evaporator above in
1-part version*

*Evaporator in centre in
2-part version*

Control system



The banquet trolley for cold food

The temperature can be regulated from -12 °C to +8 °C by means of a thermostat, with memory function.

Units are ready for connection with a 2 m spiral cable, earthed plug and cable holder. Rustproof castors in accordance with DIN 18867 Part 8, wheel diameter 200 mm, 2 fixed castors and 2 swivel castors with brake. Rated voltage 1 N AC 230 V 50 Hz.




BKW-KF 1 x 2/1 GN refrigerated

Dimensions	804 x 884 x 1755 mm
Empty weight	150 kg
Total connected load	600 Watt
Storage capacity*	 
Plates not stacked	
ø 260 mm	40 (4 per grille)
ø 310 mm	20 (2 per grille)
Clearance between rails	115 mm
Max. no. of stainless steel grilles GN 2/1	10
Order no.	88 23 04 02

BKW-KF 2 x 2/1 GN refrigerated

Dimensions	1487 x 884 x 1755 mm
Empty weight	215 kg
Total connected load	600 Watt
Storage capacity*	   
Plates not stacked	
ø 260 mm	88 (4 per grille)
ø 310 mm	44 (2 per grille)
Clearance between rails	115 mm
Max. no. of stainless steel grilles GN 2/1	2 x 11
Order no.	88 23 04 01



Rail clearance:

Describes the maximum useful height between the shelves

* Size of stainless steel grilles: 650 x 530 mm; the grilles are also suitable for smaller plates, dessert bowls, bottles etc.



*Traditional simple castors:
Hard impacts are directly transferred*

Your food is better protected on spring-loaded castors



Spring-loaded double castors:
Hard impacts are softened

Canteen units are heavily used; however until now little attention has been paid to the comfort of the castors although using spring-loaded double castors can make a significant difference. Spring-loaded double castors (wheel diameter 150 mm) provide twice the wheel contact and therefore reduce the castor resistance. Small bumps on the floor are balanced out and the integrated springs reduce the hard impacts.

The benefits are obvious: Easier handling thanks to less castor resistance, quiet operation thanks to low noise emission and gentler transportation of loaded menu plates. The transported food is treated with more care and remains appetising for longer. The spring-loaded double casters are available as an accessory for banquet trolleys. Just ask us!

**Quality
which stands for itself**



Technical details

Accessories:

Electrically driven:

Steered using additional twist handles on both sides. There are two possible speeds forwards and backwards. There is also an emergency off switch as a safety precaution. Just ask us!

All-round top gallery for heated banquet trolley

Recessed pushing handle for heated banquet trolley

All-round bumper





Accessories

Stainless steel bowl cover,

single-walled, matt, with hole,
with groove for deep soup bowl,
dia. 265 mm, height 49 mm,
weight 410 g

Order no. 89080131

Stainless steel grille

Size 2/1, weight approx. 2.3 kg,
load capacity approx. 80 kg for
even loads

Order no. 84140101

Stainless steel plate carrier

for 6 portioned plates
up to ø 260 mm

Order no. 88230501

Stainless steel bowl cover,

single-walled, polished, with hole,
with groove for deep soup bowl,
dia. 265 mm, height 49 mm,
weight 410 g

Order no. 89080331

Stainless steel grille


Size 2/1, lightweight version,
weight approx. 1.5 kg,
load capacity approx. 60 kg for
even loads

Order no. 84140106



Gastronorm containers

see extra brochure



***Hungry for more?
We will be glad to advise you.***

Germany

Rieber GmbH & Co. KG
Hoffmannstraße 44
D-72770 Reutlingen
Fon [0 71 21] 5 18-0
Fax [0 71 21] 5 18-302
E-Mail: info@rieber.de
www.rieber.de

Austria

Rieber + Grohmann GesmbH.
Seybelgasse 13
A-1230 Wien
Fon [01] 865 15 10
Fax [01] 865 15 10-10
E-Mail: office@at.rieber.de
www.rieber.de

Switzerland

Rieber ag
Handelszentrum Schöntal
Rorschacher Strasse
Postfach 118
CH-9402 Mörschwil
Fon [0 71] 868 93 93
Fax [0 71] 866 27 37
E-Mail: mail@rieber.ch
www.rieber.ch

Great Britain

BGL-Rieber Ltd.
Unit 6 Lancaster Park
Industrial Estate, Bowerhill,
Melksham
GB-Wiltshire SN12 6TT
Fon [0 12 25] 70 44 70
Fax [0 12 25] 70 59 27
E-Mail: bgl.melksham@ic24.net
www.rieber.de

The Netherlands

Rieber Benelux B.V.
»Kantorenhuis«
Schipholweg 76
NL-2316 XD Leiden
Fon [0 71] 5 23 01 70
Fax [0 71] 5 23 45 80
E-Mail: jerry.hol@nl.rieber.de
www.rieber.de

France

Rieber SARL
8, rue du Périgord
B.P. 37
F-68272 Wittenheim Cedex
Fon [03] 89 62 50 60
Fax [03] 89 57 17 94
E-Mail: robert.schlecht@fr.rieber.de
www.rieber.de

Poland

Gastromedia Sp.z o.o.
ul. Sobocka 19
PL-01-684 Warszawa
Fon [0 22] 8 33 87 07
Fax [0 22] 8 33 87 22
E-Mail: gastro@gastromedia.pl
www.gastromedia.pl

Tanake S.A.
ul. Puławska 426
PL-02-884 Warszawa
Fon [0 22] 3 36 90 00
Fax [0 22] 3 36 90 09
E-Mail: tanake@tanake.com.pl
www.tanake.com.pl

The Czech Republic

Rieber spol.s.r.o.
Velkokuchyňská zařízení
Hradecká 3/2526
CZ-131 00 Praha 3 - Vinohrady
Fon [02] 72 73 14 43
Fax [02] 72 73 14 44
E-Mail: rieber@rieber.cz
www.rieber.cz



Order the brochure about our
Thermoports® of the 2-★ or
3-★★★ category ...

... or about our Gastronorm
containers.

Rieber
[the right solution]